

**BREMAXX® outdoor extension cable (20m cable in red, for short-term outdoor use IP44, can be used down to -35 °C, oil and UV-resistant)**



## Product specifications BN1161760:

|                               |                               |                |    |
|-------------------------------|-------------------------------|----------------|----|
| Automatically retractable     | No                            | USB connection | No |
| Cable length                  | 20.0 m                        |                |    |
| Cable type                    | AT-N05V3V3-F<br>3G1.5         |                |    |
| Colour                        | Red                           |                |    |
| Conductor diameter            | 3 x 1.50 mm <sup>2</sup>      |                |    |
| Conductor material            | Copper                        |                |    |
| Indoor / outdoor              | Indoor & Outdoor              |                |    |
| IP rating                     | IP44                          |                |    |
| Number of outputs             | 1                             |                |    |
| Number of products in package | 1 pcs                         |                |    |
| Number of sockets             | 1 pcs                         |                |    |
| Power plug                    | Euro / Type-C<br>(CEE 7/17)   |                |    |
| Power source type             | Mains Powered                 |                |    |
| Socket type                   | 1x Plug with earth<br>contact |                |    |

## Packaging information:

|                    |               |
|--------------------|---------------|
| Brand              | Brennenstuhl  |
| Order code         | BN-1161760    |
| EAN single Product | 4007123186006 |
| EAN Inner Carton   |               |
| EAN Outer Carton   |               |
| Packaging          | Wrap          |
| Package contents   |               |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 230 mm | 90 mm  | 230 mm | 2260 g  |
| 2        | 265 mm | 180 mm | 250 mm | 4820 g  |
| 5        | 300 mm | 220 mm | 390 mm | 10500 g |

