nedis Datasheet | Smoke Alarm

Battery Powered | Battery life up to: 1 year | Linkable | EN 14604 | With test button | 85 dB | ABS | White

Brand: Nedis | Article number: DTCTSC10WT2 | Product EAN number: 5412810269181

Battery life up toI yearBattery type9V BlockBattery typeAACertification markcColourWhiteDetector typeSmokeDameter127 mmFaquency range433.05 + 434.79 MHzIncludes mounting materialYesInput voltage9V DCLinkableYesMaximum linkable alarmsMainteratNumber of products in package101 and °CNumber of products in package104 and °CPover source typeBattery PoweredRadio transmit power7.84 dB/mRadio transmit power10 yearSoundSourdSoundStallWith pause buttonMainteratWith pause buttonNoWith test buttonYes	Product specifications			
AACertification markceColourWhiteDetector typeSmokeDiameter127 mmDiameterKin 14604Frequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaterialUnlimitedMasuring range0 - 3 mNumber of products in package10 - 40 °CPower source typeBattery PoweredRequired batteries (included)2x 9V/GF22Sound10 yearSoundSourgWith pause buttonKai MHz	Battery life up to	1 year		
International problemCertification markceColourWhiteDetector typeSmokeDiameter127 mmEN-compliantEN 14604Frequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCInkableYesMaterialABSMaximum linkable alarmsUnlimitedNumber of products in package10 - 40 °CPower source typeBattery PoweredRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSoundSa Sd BWith pause buttonKa S MHz	Battery type	9V Block		
ColourWhiteColourWhiteDetector typeSmokeDiameter127 mmEN-compliantEN 14604Frequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedNumber of products in package10 - 40 °CPower source typeBattery PoweredRadio transmit power1.94 dB/mRadio transmit powerSA AdLR6Sound10 yearSoundSourgeWith pause buttonKa Si MHzWith pause buttonNo		AA		
NumberDetector typeSmokeDiameter127 mmEN-compliantEN 14604Frequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedNumber of products in package10 - 40 °CPower source typeBattery PoweredRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSoundSouthSupported wireless technologyKa3 MHzWith pause buttonNo	Certification mark	ce		
Diameter127 mmDiameter127 mmEN-compliantEN 14604Frequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mOperating temperature range10 - 40 °CPower source typeBattery PoweredRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSoundSouthSupported wireless technologyA33 MHzWith pause buttonNo	Colour	White		
EnditionEnditionEN-compliantEN 14604Frequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedNumber of products in package10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)Sx 9V/GF22Sound10 yearSoundSd BWith pause buttonNo	Detector type	Smoke		
Frequency range433.05 - 434.79 MHzFrequency range433.05 - 434.79 MHzIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mOperating temperature range10 - 40 °CPower source typeBattery PoweredRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Diameter	127 mm		
Incluency largeReference in the numberIncludes mounting materialYesInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mNumber of products in package1 pcsOperating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technologyKa3 MHzWith pause buttonNo	EN-compliant	EN 14604		
Input voltage9 V DCInput voltage9 V DCLinkableYesMaterialABSMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mNumber of products in package10 - 40 °COperating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/GF22Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Frequency range	433.05 - 434.79 MHz		
LinkableYesLinkableKesMaterialABSMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mNumber of products in package1 pcsOperating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technologyKa3 MHzWith pause buttonNo	Includes mounting material	Yes		
AnsatzABSMaterialABSMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mNumber of products in package1 pcsOperating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Input voltage	9 V DC		
Maximum linkable alarmsUnlimitedMaximum linkable alarmsUnlimitedMeasuring range0 - 3 mNumber of products in package1 pcsOperating temperature range-10 - 40 ° CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Linkable	Yes		
Measuring range0 - 3 mNumber of products in package1 pcsOperating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Material	ABS		
Number of products in package1 pcsOperating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Maximum linkable alarms	Unlimited		
Operating temperature range-10 - 40 °CPower source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Gr AA/LR66x AA/LR6Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Measuring range	0 - 3 m		
Power source typeBattery PoweredRadio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F22Sensor life cycle6x AA/LR6Sound85 dBSupported wireless technology433 MHzWith pause buttonNo	Number of products in package	1 pcs		
Radio transmit power7.84 dB/mRequired batteries (included)2x 9V/6F226x AA/LR66x AA/LR6Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Operating temperature range	-10 - 40 °C		
Required batteries (included) 2x 9V/6F22 6x AA/LR6 Sensor life cycle 10 year Sound 85 dB Supported wireless technology 433 MHz With pause button No	Power source type	Battery Powered		
6x AA/LR6Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Radio transmit power	7.84 dB/m		
Sensor life cycle10 yearSound85 dBSupported wireless technology433 MHzWith pause buttonNo	Required batteries (included)	2x 9V/6F22		
Sound85 dBSupported wireless technology433 MHzWith pause buttonNo		6x AA/LR6		
Supported wireless technology 433 MHz With pause button No	Sensor life cycle	10 year		
With pause button No	Sound	85 dB		
	Supported wireless technology	433 MHz		
With test button Yes	With pause button	No		
	With test button	Yes		

Packaging information					
Brand	Nedis	Nedis			
Order code	DTCTSC	DTCTSC10WT2			
EAN single product:	541281	5412810269181			
EAN Inner carton:					
EAN Outer carton:	541281	5412810378968			
Packaging	Giftbox	Giftbox with eurolock			
Package contents	■ 2x sm	2x smoke detector			
	■ 2x 9-	• 2x 9-V battery			
Quantity	Lx	W x	H (mm)	Weight	
1	115 mm	165 mm	135 mm	628 g	
12	380 mm	150 mm	550 mm	7980 g	







Nedis.co.uk/DTCTSC10WT2