

Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 3.00 m | Round | PVC | Black | Envelope



Product specifications CSGP40000BK30:

| Cable design | Round | | |
|---------------------------|--------------------------------|--|--|
| Cable length | 3.00 m | | |
| Cable mantle material | PVC | | |
| Cable mantle size | 5.0 mm | | |
| Cable type | Coax | | |
| Colour | Black | | |
| Conductor diameter | 0.50 mm | | |
| Conductor material | CCS | | |
| Connector A | IEC (Coax) Male | | |
| Connector B | IEC (Coax) Female | | |
| Connector design - side A | Straight | | |
| Connector design - side B | Straight | | |
| Connector material | PVC Nickel Plated 2.7 mm | | |
| Connector plating | | | |
| Dielectric diameter | | | |
| Impedance | 75 Ohm | | |

| Insulation material | PE | |
|-------------------------------|-----------------|--|
| Material | PVC | |
| Number of products in package | 1 pcs | |
| Packaging | Envelope | |
| Shielding | Double Shielded | |
| Signal to Noise Ratio | 90 dB | |

Packaging information:

| Brand | Nedis |
|--------------------|--------------------|
| Order code | CSGP40000BK30 |
| EAN single Product | 5412810281824 |
| EAN Inner Carton | 5412810361892 |
| EAN Outer Carton | 5412810348138 |
| Packaging | Envelope |
| Package contents | 1x Coax Cable 90dB |

| Quantity | Lx | Wx | H (mm) | Weight |
|----------|--------|--------|--------|---------|
| 1 | 30 mm | 225 mm | 150 mm | 99 g |
| 50 | 335 mm | 175 mm | 475 mm | 5180 g |
| 100 | 345 mm | 370 mm | 490 mm | 10980 g |



