

Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 90 dB | 75 Ohm | Double Shielded 15.0 m | Round | PVC | White | Envelope

Product specifications CSGP40000WT150:

| Cable design | Round | |
|---------------------------|-------------------|--|
| Cable length | 15.0 m | |
| Cable mantle material | PVC | |
| Cable mantle size | 5.0 mm | |
| Cable type | Coax | |
| Colour | White | |
| Conductor diameter | 0.50 mm | |
| Conductor material | CCS | |
| Connector A | IEC (Coax) Male | |
| Connector B | IEC (Coax) Female | |
| Connector design - side A | Straight | |
| Connector design - side B | Straight | |
| Connector material | PVC | |
| Connector plating | Nickel Plated | |
| Dielectric diameter | 2.7 mm | |
| Impedance | 75 Ohm | |

| Insulation material | PE |
|-------------------------------|-----------------|
| Material | PVC |
| Number of products in package | 1 pcs |
| Packaging | Envelope |
| Shielding | Double Shielded |
| Signal to Noise Ratio | 90 dB |



Datasheet | Coax Cable | CSGP40000WT150



Packaging information:

| Brand | Nedis |
|--------------------|--------------------|
| Order code | CSGP40000WT150 |
| EAN single Product | 5412810281893 |
| EAN Inner Carton | 5412810398126 |
| EAN Outer Carton | 5412810348176 |
| Packaging | Envelope |
| Package contents | 1x Coax Cable 90dB |

| Quantity | Lx | W x | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 62 mm | 230 mm | 133 mm | 380 g |
| 1 | 40 mm | 330 mm | 225 mm | 368 g |
| 20 | 370 mm | 240 mm | 410 mm | 9120 g |

