



Datasheet | Coax Cable

IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 2.00 m | Round | PVC | White | Envelope

Brand: Nedis | Article number: CSGP40020WT20 | Product EAN number: 5412810282098

Product specifications

| | |
|-------------------------------|--------------------------|
| Cable design | Round |
| Cable length | 2.00 m |
| Cable mantle material | PVC |
| Cable mantle size | 6.0 mm |
| Cable type | Coax |
| Colour | White |
| Conductor diameter | 0.50 mm |
| Conductor material | OFC |
| Connector A | IEC (Coax) Male |
| Connector B | IEC (Coax) Female |
| Connector design - side A | Straight |
| Connector design - side B | Straight |
| Connector material | PVC |
| Connector plating | Nickel Plated |
| Dielectric diameter | 3.1 mm |
| Impedance | 75 Ohm |
| Insulation material | PE |
| Material | PVC |
| Number of products in package | 1 pcs |
| Packaging | Envelope |
| Shielding | Quad Shielded |
| Signal to Noise Ratio | 120 dB |

Packaging information

| | |
|---------------------|----------------------------|
| Brand | Nedis |
| Order code | CSGP40020WT20 |
| EAN single product: | 5412810282098 |
| EAN Inner carton: | 5412810362004 |
| EAN Outer carton: | 5412810348244 |
| Packaging | Envelope |
| Package contents | 1x Coax Cable 120dB |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|---------|
| 1 | 30 mm | 230 mm | 55 mm | 115 g |
| 50 | 250 mm | 335 mm | 300 mm | 6200 g |
| 100 | 310 mm | 355 mm | 510 mm | 13060 g |

