

**Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 5.00 m | Round | PVC | Black | Polybag**



**Product specifications CSGP40120BK50:**

Cable design	Round	Insulation material	PE
Cable length	5.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	6.0 mm	Packaging	Polybag
Cable type	Coax	Shielding	Quad Shielded
Colour	Black	Signal to Noise Ratio	120 dB
Conductor diameter	0.50 mm		
Conductor material	OFC		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Angled 90°		
Connector design - side B	Angled 90°		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	3.1 mm		
Impedance	75 Ohm		

**Packaging information:**

Brand	Nedis
Order code	CSGP40120BK50
EAN single Product	5412810282203
EAN Inner Carton	
EAN Outer Carton	5412810369829
Packaging	Polybag
Package contents	1x Coax Cable 120dB

Quantity	L x	W x	H (mm)	Weight
1	210 mm	40 mm	210 mm	231 g
50	500 mm	220 mm	500 mm	13260 g

