

## Datasheet | Coax Cable

## IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 20.0 m | Round | PVC | White | Polybag

Brand: Nedis | Article number: CSGP40120WT200 | Product EAN number: 5412810282241

Product specifications  Cable design Round  Cable length 20.0 m  Cable mantle material PVC  Cable mantle size 6.0 mm  Cable type Coax  Colour White  Conductor diameter 0.50 mm  Conductor material OFC  Connector A IEC (Coax) Male  Connector B IEC (Coax) Female  Connector design - side A Angled 90°  Connector material PVC  Connector plating Nickel Plated  Dielectric diameter 3.1 mm  Impedance 75 Ohm  Insulation material PVC  Number of products in package 1 pcs  Packaging Polybag  Signal to Noise Ratio 120 dB		
Cable length Cable mantle material PVC Cable mantle size 6.0 mm Cable type Coax Colour White Conductor diameter Conductor material OFC Connector A IEC (Coax) Male Connector B IEC (Coax) Female Connector design - side A Angled 90° Connector material PVC Connector plating Dielectric diameter Insulation material PVC Number of products in package Polybag Shielding  Quad Shielded	Product specifications	
Cable mantle material PVC Cable mantle size G.0 mm Cable type Coax  Colour White Conductor diameter O.50 mm Conductor material OFC Connector A IEC (Coax) Male Connector B IEC (Coax) Female Connector design - side A Angled 90° Connector material PVC Connector material PVC Connector plating Dielectric diameter Impedance Insulation material PE Material Material PVC Number of products in package Polybag Shielding PVC Quad Shielded	Cable design	Round
Cable mantle size Cable type Coax Colour White Conductor diameter Conductor material Connector A Connector B Connector design - side A Connector design - side B Connector plating Dielectric diameter Insulation material PE Material PVC Number of products in package Polybag Shielding  Coax White Coax HEC (Coax) Male HEC (Coax) Female Angled 90° Angled 90° Nickel Plated Nickel Plated PVC Number of products in package Polybag Quad Shielded	Cable length	20.0 m
Cable type Coax Colour White Conductor diameter O.50 mm Conductor material OFC Connector A IEC (Coax) Male IEC (Coax) Female Connector design - side A Connector design - side B Connector material PVC Connector plating Dielectric diameter Insulation material PE Material PVC Number of products in package Polybag Shielding Consector plating Postor material PC Rome PC Rome Rome Rome Rome Rome Rome Rome Rome	Cable mantle material	PVC
Colour  Conductor diameter  Conductor material  Connector A  Connector B  Connector design - side A  Connector material  Connector design - side B  Connector material  Connector plating  Dielectric diameter  Impedance  Insulation material  Material  Number of products in package  Polybag  Shielding  More  Conductor diameter  D. So ome diameter  Nickel Plated  3.1 mm  PE  PVC  Puc  1 pcs  Polybag  Quad Shielded	Cable mantle size	6.0 mm
Conductor diameter  Conductor material  Connector A  Connector B  Connector design - side A  Connector design - side B  Connector material  Connector plating  Dielectric diameter  Impedance  Insulation material  Material  Number of products in package  Polybag  Shielding  OFC  IEC (Coax) Male  IEC (Coax) Female  Regular  IEC (Coax) Female  Angled 90°  Angled 90°  Nickel Plov  Angled 90°  Nickel Plated  3.1 mm  PE  PE  PUC  1 pcs  Polybag  Quad Shielded	Cable type	Coax
Conductor material  Connector A  IEC (Coax) Male  IEC (Coax) Female  Connector design - side A  Connector design - side B  Connector material  PVC  Connector plating  Dielectric diameter  Insulation material  PE  Material  PVC  Number of products in package  Polybag  Shielding  OFC  IEC (Coax) Male  IEC (Coax) Female  Angled 90°  Angled 90°  Nickel Plated  3.1 mm  75 Ohm  PE  PVC  1 pcs  Polybag  Quad Shielded	Colour	White
Connector A  Connector B  Connector B  Connector design - side A  Connector design - side B  Connector material  Connector plating  Dielectric diameter  Insulation material  Material  Puc  Number of products in package  Polybag  Ponnector A  IEC (Coax) Male  Angled 90°  Angled 90°  Nickel Plated  3.1 mm  PE  PUC  Puc  Puc  1 pcs  Packaging  Polybag  Quad Shielded	Conductor diameter	0.50 mm
Connector B  Connector design - side A  Connector design - side B  Connector material  Connector plating  Dielectric diameter  Impedance  Insulation material  Material  Mumber of products in package  Packaging  Piec (Coax) Female  Angled 90°  Angled 90°  Nickel Plated  Nickel Plated  3.1 mm  PE  PE  PUC  Number of products in package  Polybag  Shielding  Quad Shielded	Conductor material	OFC
Connector design - side A  Connector design - side B  Angled 90°  Connector material  PVC  Connector plating  Dielectric diameter  Impedance  Insulation material  Material  PE  Material  PVC  Number of products in package  Packaging  Shielding  Angled 90°  Nickel Plated  Nickel Plated  Pto  Nickel Plated  Pto  Pto  Pto  1 pcs  Polybag  Quad Shielded	Connector A	IEC (Coax) Male
Connector design - side B  Connector material  PVC  Connector plating  Dielectric diameter  Impedance  Insulation material  Material  Number of products in package  Packaging  Shielding  Angled 90°  Nickel Plated  3.1 mm  PE  PE  PVC  1 pcs  Polybag  Quad Shielded	Connector B	IEC (Coax) Female
Connector material PVC Connector plating Nickel Plated Dielectric diameter 3.1 mm Impedance 75 Ohm Insulation material PE Material PVC Number of products in package 1 pcs Packaging Polybag Shielding Quad Shielded	Connector design - side A	Angled 90°
Connector plating  Dielectric diameter  Janu Impedance  75 Ohm Insulation material  Material  Puc Number of products in package  Packaging  Polybag  Shielding  Nickel Plated  Pte  Pte  Pte  1 pcs  Polybag  Quad Shielded	Connector design - side B	Angled 90°
Dielectric diameter 3.1 mm  Impedance 75 Ohm  Insulation material PE  Material PVC  Number of products in package 1 pcs  Packaging Polybag  Shielding Quad Shielded	Connector material	PVC
Impedance 75 Ohm Insulation material PE Material PVC Number of products in package 1 pcs Packaging Polybag Shielding Quad Shielded	Connector plating	Nickel Plated
Insulation material PE  Material PVC  Number of products in package 1 pcs  Packaging Polybag  Shielding Quad Shielded	Dielectric diameter	3.1 mm
Material PVC Number of products in package 1 pcs Packaging Polybag Shielding Quad Shielded	Impedance	75 Ohm
Number of products in package 1 pcs Packaging Polybag Shielding Quad Shielded	Insulation material	PE
Packaging Polybag Shielding Quad Shielded	Material	PVC
Shielding Quad Shielded	Number of products in package	1 pcs
	Packaging	Polybag
Signal to Noise Ratio 120 dB	Shielding	Quad Shielded
	Signal to Noise Ratio	120 dB

Packaging information				
Brand	Nedis			
Order code	CSGP40120WT200			
EAN single product:	5412810282241			
EAN Inner carton:	5412810392957			
EAN Outer carton:	5412810369843			
Packaging	Polybag			
Package contents	1x Coax Cable 120dB			

Quantity	Lx	Wx	H (mm)	Weight
1	175 mm	55 mm	260 mm	805 g
10	310 mm	290 mm	250 mm	7998 g
20	335 mm	310 mm	505 mm	17400 g





