

**Coax Cable | IEC (Coax) Male | IEC (Coax) Male | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 2.00 m | Round | PVC | White | Envelope**



**Product specifications CSGP40200WT20:**

Cable design	Round	Insulation material	PE
Cable length	2.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	5.0 mm	Packaging	Envelope
Cable type	Coax	Shielding	Double Shielded
Colour	White	Signal to Noise Ratio	90 dB
Conductor diameter	0.50 mm		
Conductor material	CCS		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Male		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	2.7 mm		
Impedance	75 Ohm		

**Packaging information:**

Brand	Nedis
Order code	CSGP40200WT20
EAN single Product	5412810281961
EAN Inner Carton	5412810362103
EAN Outer Carton	5412810348343
Packaging	Envelope
Package contents	1x Coax Cable 90dB

Quantity	L x	W x	H (mm)	Weight
1	30 mm	230 mm	110 mm	65 g
50	435 mm	90 mm	485 mm	3500 g
200	380 mm	355 mm	455 mm	13980 g

