

## Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 90 dB | 75 Ohm | Double Shielded 1.50 m | Round | PVC | White | Polybag

## Product specifications CSGP40100WT15:

| Cable design              | Round             |
|---------------------------|-------------------|
| Cable length              | 1.50 m            |
| Cable mantle material     | PVC               |
| Cable mantle size         | 5.0 mm            |
| Cable type                | Coax              |
| Colour                    | White             |
| Conductor diameter        | 0.50 mm           |
| Conductor material        | CCS               |
| Connector A               | IEC (Coax) Male   |
| Connector B               | IEC (Coax) Female |
| Connector design - side A | Angled 90°        |
| Connector design - side B | Angled 90°        |
| Connector material        | PVC               |
| Connector plating         | Nickel Plated     |
| Dielectric diameter       | 2.7 mm            |
| Impedance                 | 75 Ohm            |

| Insulation material   | PE            |
|-----------------------|---------------|
| Material              | PVC           |
| Packaging             | Polybag       |
| Shielding             | Double Shield |
| Signal to Noise Ratio | 90 dB         |





## Packaging information:

| Brand              | Nedis              |
|--------------------|--------------------|
| Order code         | CSGP40100WT15      |
| EAN single Product | 5412810282258      |
| EAN Inner Carton   |                    |
| EAN Outer Carton   | 5412810369805      |
| Packaging          | Polybag            |
| Package contents   | 1x Coax Cable 90dB |
|                    |                    |

| Quantity | Lx     | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 110 mm | 30 mm  | 225 mm | 50 g    |
| 200      | 380 mm | 350 mm | 450 mm | 10900 g |



lded