Datasheet | LED Batten Light | BTTN43W120

LED Batten Light | 1200 mm | 4400 lm | 4000 K | 43 W | IP65



Product specifications BTTN43W120:

| Adjustment possibilities | Not adjustable | | |
|-----------------------------------|----------------------------|--|--|
| Beam angle | 125 ° | | |
| Body material | Polycarbonate | | |
| Colour | White | | |
| Colour consistency (SDCM) | ≤ 6 | | |
| Colour rendering index (Ra) | ≥ 80 | | |
| Colour temperature | 4000 K | | |
| Dimmable | No | | |
| Energy class | A+ | | |
| Energy consumption per 1000 hours | 43 kWh | | |
| Especially for bathroom | No | | |
| Indoor / outdoor | Indoor | | |
| Input voltage | 220 - 240 V AC 50/60 Hz | | |
| Interconnactable | Yes, per type | | |
| IP rating | IP65 | | |
| Lamp finish | Clear | | |

| Integrated | | |
|-----------------------------|--|--|
| 1200 mm | | |
| Cool White | | |
| Wall Switch | | |
| 70.0 % | | |
| Polycarbonate | | |
| 43 W | | |
| No | | |
| 1 pcs | | |
| ≥ 20000 Switching Cycles | | |
| -20 - 50 °C | | |
| Ceiling | | |
| Wall | | |
| ≥ 0.9 | | |
| Mains Powered | | |
| 25000 h | | |
| | | |

| Rated luminous flux | 4400 lm |
|---------------------------------|--------------------------|
| Rated Peak Intensity in Candela | N/A |
| Starting time | 0.5s |
| Technology | LED |
| Warm-up time to 60% light | Instant Full Light (1 s) |
| Wattage | 43 W |
| Wattage equivalent | 247 W |

Packaging information:

| Brand | Nedis |
|--------------------|--------------------|
| Order code | BTTN43W120 |
| EAN single Product | 5412810287697 |
| EAN Inner Carton | |
| EAN Outer Carton | 5412810377176 |
| Packaging | Wrap |
| Package contents | Batten fixture |
| | Mounting materials |

Read more online

| Quantity | Lx | Wx | H (mm) | Weight |
|----------|--------|--------|---------|-------------|
| 1 | 90 mm | 70 mm | 1245 mm | า 1100 g |
| 6 | 285 mm | 160 mm | 1255 mm | า 7420 g |



