


**Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 3.00 m | Round | PVC | White | Box**



**Product specifications CSGB40000WT30:**

Cable design	Round	Insulation material	PE
Cable length	3.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	5.0 mm	Packaging	Box
Cable type	Coax	Shielding	Double Shielded
Colour	White	Signal to Noise Ratio	90 dB
Conductor diameter	0.50 mm		
Conductor material	CCS		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	2.7 mm		
Impedance	75 Ohm		

**Packaging information:**

Brand	Nedis
Order code	CSGB40000WT30
EAN single Product	5412810289424
EAN Inner Carton	5412810343089
EAN Outer Carton	5412810340767
Packaging	Box
Package contents	1x Coax Cable 90 dB

Quantity	L x	W x	H (mm)	Weight
1	30 mm	230 mm	55 mm	97 g
10	75 mm	245 mm	320 mm	1028 g
60	235 mm	510 mm	340 mm	6500 g

