

Coax Cable | IEC (Coax) Male | IEC (Coax) Male | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 5.00 m | Round | PVC | Blister



Product specifications CSGB40200WT50:

Cable design	Round	Material	PVC
Cable length	5.00 m	Packaging	Blister
Cable mantle material	PVC	Shielding	Double Shielded
Cable mantle size	5.0 mm	Signal to Noise Ratio	90 dB
Cable type	Coax		
Conductor diameter	0.50 mm		
Conductor material	CCS		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Male		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	2.7 mm		
Impedance	75 Ohm		
Insulation material	PE		

Packaging information:

Brand	Nedis
Order code	CSGB40200WT50
EAN single Product	5412810289493
EAN Inner Carton	5412810392858
EAN Outer Carton	5412810369638
Packaging	Blisterbox
Package contents	1x Coax Cable 90 dB

Quantity	L x	W x	H (mm)	Weight
1	65 mm	230 mm	80 mm	174 g
5	85 mm	235 mm	315 mm	966 g
30	280 mm	490 mm	340 mm	6350 g

