

Datasheet | Walkie-Talkie Set

2 Handsets | Up to 5 km | Frequency channels: 8 | PTT / VOX | up to 2.5 Hours | Black

Brand: Nedis | Article number: WLTK0500BK | Product EAN number: 5412810309719

Automatic battery saving mode Automatic channel scan Battery level indicator Battery type Bett clips included Colour Black Communication method PTT VOX CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material ABS Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Maximum transmit power Number of call tones Number of products in package Operating teme Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size AAA AAAA AAA AAA AAA AAA AAA AAA AAA	Product specifications			
Automatic channel scan Battery level indicator Battery type Belt clips included Colour Black Communication method PTT VOX CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package PMR446 license free Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size PMAAA AAA Yes AAAA AAA AAA Yes AAA AAA	Automatic battery saving mode	Yes		
Battery type Belt clips included Colour Black Communication method PTT VOX CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating teme Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size AAA PTT Vox Vox Black PTT VOX VOX 38 BRE Green BAB ABS O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 2.5 Hours Up to 2.5 Hours Up to 5 km Up to 5 km Up to 1.5 km Up to 1.5 km 24 hrs O dBi 25 dBm 10 Voy Vox Vox AAA VRO3 Vox Vox Vox ABS AAA VRO3 Vox Vox ABA VAAA VRO3 Vox AAA VRO3 VOX AAA VRO3 VOX VOX ABA VAAA VAAA VAAA VAAA VAAA VAAA VAAA	Automatic channel scan			
Battery type Belt clips included Colour Black Communication method PTT VOX CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating teme Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size AAA PTT Vox Vox Black PTT VOX VOX 38 BRE Green BAB ABS O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 2.5 Hours Up to 2.5 Hours Up to 5 km Up to 5 km Up to 1.5 km Up to 1.5 km 24 hrs O dBi 25 dBm 10 Voy Vox Vox AAA VRO3 Vox Vox Vox ABS AAA VRO3 Vox Vox ABA VAAA VRO3 Vox AAA VRO3 VOX AAA VRO3 VOX VOX ABA VAAA VAAA VAAA VAAA VAAA VAAA VAAA	Battery level indicator			
Belt clips included Colour Black Communication method PTT VOX CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating teme Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size PMT VOX 38 Green FTT VOX 38 0.166 W/kg for FM 12.5 KHz up to 2.5 Hours Up to 2.5 Hours Up to 2.5 Hours Up to 2.5 Hours Up to 5 km Up to 1.5 km Up to 1.5 km 24 hrs 0 dBi 25 dBm 10 27 Landsets 28 Landsets 29 pcs 29 pcs 38 Required batteries (not included) Screen size	,			
Colour Communication method Communication method PTT VOX CTCSS codes (for private talking) Display colour Frequency channels Headphone output No LED light Material ABS Max. SAR values O.166 W/kg for FM 12.5 KHz Maximum battery operating time Up to 2.5 Hours Maximum range (normal use / downtown or resid Maximum range (urban areas / country side) Maximum standby time Up to 1.5 km Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size Display Required batteries (not included) Screen size Required batteries (not included) Screen size PMR VOX 38 Required batteries (not included) ABS O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 2.5 Hours Up to 5 km Up to 1.5 km Up to 1.5 km Up to 1.5 km 24 hrs 0 dBi 25 dBm 10 26 dBm 10 27 - 55 °C 28 PMR446 license free Pes Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size				
CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating teme Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size Mood Resid No Ves ABS O.166 W/kg for FM 12.5 KHz up to 2.5 Hours Up to 2.5 Hours Up to 200-500 m Up to 1.5 km Up to 1.5 km O dBi 24 hrs O dBi 2 Handsets 2 pcs Operating temperature range -20 - 55 °C Yes Power source type Battery Powered Frivacy codes (CTCSS + DCS) Required batteries (not included) Screen size	Colour			
CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size No No No Yes ABS O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 2.5 Hours Up to 200-500 m Up to 5 km Up to 1.5 km O dBi 24 hrs O dBi 2 Handsets 2 pcs Operating temperature range -20 - 55 ° C Yes Power source type Battery Powered Frivacy codes (CTCSS + DCS) Required batteries (not included) Screen size	Communication method			
CTCSS codes (for private talking) Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size No No No Yes ABS O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 2.5 Hours Up to 200-500 m Up to 5 km Up to 1.5 km O dBi 24 hrs O dBi 2 Handsets 2 pcs Operating temperature range -20 - 55 ° C Yes Power source type Battery Powered Frivacy codes (CTCSS + DCS) Required batteries (not included) Screen size		VOX		
Display colour Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 200-500 m Up to 5 km Up to 1.5 km OdBi 24 hrs O dBi 26 dBm 10 Yes Power 5° °C Yes Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size	CTCSS codes (for private talking)			
Frequency channels Headphone output LED light Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Maximum transmit power Number of call tones Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 200-500 m Up to 1.5 km Up to 1.5 km Up to 1.5 km 24 hrs O dBi 25 dBm 10 27 Handsets 28 Handsets 29 pcs 29 pcs 38 Battery Powered 38 Gx AAA/LRO3 0.9 "				
Headphone output LED light Yes Material ABS Max. SAR values O.166 W/kg for FM 12.5 KHz Maximum battery operating time Up to 2.5 Hours Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Up to 1.5 km Maximum standby time Aximum transmit antenna gain Maximum transmit power Number of call tones Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 200-500 m Up to 1.5 km Up to 1.5 km 2 Handsets 2 pcs 7 C Yes Battery Powered 6 x AAA/LR03 0.9 "				
Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Privacy codes (CTCSS + DCS) Required batteries (not included) O.166 W/kg for FM 12.5 KHz Up to 2.5 Hours Up to 200-500 m Up to 5 km Up to 1.5 km OdBi 24 hrs OdBi 26 dBm 10 21 Handsets 2 pcs Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size	. ,	-		
Material Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size O.166 W/kg for FM 12.5 KHz Stree FM 12.5 KHz O.166 W/kg for FM 12.5 KHz Stree FM 12.5 KHz O.166 W/kg for FM 12.5 KHz Up to 2.0-500 m Up to 200-500 m Up to 1.5 km Up to 1.5 km Up to 1.5 km 2 4 hrs O 4Bi 2 2 GBB Number of 26 dBm 10 2 Handsets 2 pcs Operating temperature range -20 - 55 °C Yes Power source type Battery Powered Fivacy codes (CTCSS + DCS) Required batteries (not included) Screen size	·			
Max. SAR values Maximum battery operating time Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Oup to 2.5 Hours Up to 200-500 m Up to 1.5 km Up to 1.5 km 24 hrs O dBi 25 dBm 10 Pundsets 2 Handsets 2 pcs -20 - 55 ° C Yes PMR446 license free Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size				
Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Maximum battery operating temperature (not included) 12.5 KHz up to 2.5 Hours Up to 200-500 m Up to 5 km Up to 1.5 km OdBi 24 hrs 0 dBi 24 hrs 26 dBm 10 27 Handsets 2 pcs Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) 6x AAA/LRO3 O.9 "	Maccia			
Maximum range (normal use / downtown or resid Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size Up to 1.5 km Up to 1.5 km Up to 1.5 km 24 hrs 0 dBi 22 handsets 2 pcs 2 pcs -20 - 55 ° C Yes Battery Powered 6x AAA/LR03 0.9 "	Max. SAR values	•		
Maximum range (open field / no obstacles) Maximum range (urban areas / country side) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size Up to 1.5 km Up to 1.5 km Up to 1.5 km La thrs OdBi Ada Alse 24 hrs OdBi Ada Alse 24 dBm 10 24 hrs 26 dBm 10 27 call tones 10 28 Handsets 29 pcs -20 - 55 °C Yes Power source type Battery Powered 6x AAA/LR03 O.9 "	Maximum battery operating time	up to 2.5 Hours		
Maximum range (urban areas / country side) Maximum standby time Maximum transmit antenna gain Maximum transmit power Number of call tones Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Up to 1.5 km 24 hrs 0 dBi 26 dBm 10 27 Handsets 2 pcs -20 - 55 °C Yes Battery Powered 38 6x AAA/LR03 0.9 "	Maximum range (normal use / downtown or resid	Up to 200-500 m		
Maximum standby time 24 hrs Maximum transmit antenna gain Maximum transmit power 26 dBm Number of call tones Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 24 hrs 24 hrs 24 hrs 26 dBm 10 27 Handsets 2 pcs 29 pcs 29 pcs 40 - 55 ° C Yes Battery Powered 6x AAA/LR03 6x AAA/LR03	Maximum range (open field / no obstacles)	Up to 5 km		
Maximum transmit antenna gain Maximum transmit power Number of call tones Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 26 dBm 10 2 Handsets 2 Handsets 2 pcs -20 - 55 °C Yes Battery Powered 38 6x AAA/LR03 0.9 "	Maximum range (urban areas / country side)	Up to 1.5 km		
Maximum transmit power Number of call tones Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 2 dBm 2 handsets 2 handsets 2 pcs -20 - 55 °C Yes Battery Powered 8 attery Powered 6 x AAA/LR03 0.9 "	Maximum standby time	24 hrs		
Number of call tones Number of handsets 2 Handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 10 2 Handsets 2 pcs -20 - 55 °C Yes Battery Powered 38 6x AAA/LR03 0.9 "	Maximum transmit antenna gain	0 dBi		
Number of handsets Number of products in package Operating temperature range Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 2 Handsets 2 pcs -20 - 55 °C Yes Battery Powered Battery Powered 6x AAA/LR03 0.9 "	Maximum transmit power	26 dBm		
Number of products in package Operating temperature range -20 - 55 °C PMR446 license free Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 2 pcs -20 - 55 °C Yes Battery Powered Battery Powered 6x AAA/LR03 0.9 "	Number of call tones	10		
Operating temperature range -20 - 55 °C PMR446 license free Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size -20 - 55 °C Yes Battery Powered 6x AAA/LR03 0.9 "	Number of handsets	2 Handsets		
PMR446 license free Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size Yes Battery Powered 6x AAA/LR03 0.9 "	Number of products in package	2 pcs		
Power source type Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size Battery Powered 6x AAA/LR03 0.9 "	Operating temperature range	-20 - 55 °C		
Privacy codes (CTCSS + DCS) Required batteries (not included) Screen size 38 6x AAA/LR03 0.9 "	PMR446 license free	Yes		
Required batteries (not included) 6x AAA/LR03 Screen size 0.9 "	Power source type	Battery Powered		
Screen size 0.9 "	Privacy codes (CTCSS + DCS)	38		
	Required batteries (not included)	6x AAA/LRO3		
Supported wireless technology 446 MHz	Screen size	0.9 "		
	Supported wireless technology	446 MHz		

Transmit frequency range	446.00625 - 446.09375 MHz
Travel case included	No
VOX levels	3

Packaging information				
Brand	Nedis			
Order code	WLTK0500BK			
EAN single product:	5412810309719			
EAN Inner carton:				
EAN Outer carton:	5412810385973			
Packaging	Giftbox			
Package contents	2x walkie talkie			
	2x belt clip			

Quantity	Lx	Wx	H (mm)	Weight
1	60 mm	150 mm	110 mm	219 g
40	325 mm	330 mm	445 mm	9300 g





