## Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Gold Plated | 75 Ohm | Quad Shielded | 2.00 m | Round | Cotton | Grey / Gun Metal Grey | Cover Window Box



## Product specifications CSTB40015WT20:

| Cable design              | Round             |  |  |
|---------------------------|-------------------|--|--|
| Cable length              | 2.00 m            |  |  |
| Cable mantle material     | Cotton            |  |  |
| Cable mantle size         | 6.6 mm            |  |  |
| Cable type                | Coax              |  |  |
| Colour                    | Grey              |  |  |
|                           | Gun Metal Grey    |  |  |
| Conductor diameter        | 0.50 mm           |  |  |
| Conductor material        | Bare Copper       |  |  |
| Connector A               | IEC (Coax) Male   |  |  |
| Connector B               | IEC (Coax) Female |  |  |
| Connector design - side A | Angled 90°        |  |  |
| Connector design - side B | Angled 90°        |  |  |
| <b>G</b>                  | 0                 |  |  |
| Connector material        | PVC               |  |  |
| -                         |                   |  |  |

| Impedance                     | 75 Ohm              |
|-------------------------------|---------------------|
| Insulation material           | PE                  |
| Material                      | Metal               |
| Number of products in package | 1 pcs               |
| Packaging                     | Cover Window<br>Box |
| Shielding                     | Quad Shielded       |

## Packaging information:

| Brand              | Nedis                 |
|--------------------|-----------------------|
| Order code         | CSTB40015WT20         |
| EAN single Product | 5412810318827         |
| EAN Inner Carton   | 5412810393008         |
| EAN Outer Carton   | 5412810370238         |
| Packaging          | Giftbox with eurolock |
| Package contents   | Coax cable            |

| Quantity | Lx     | Wx     | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1        | 30 mm  | 245 mm | 150 mm | 215 g  |
| 6        | 165 mm | 265 mm | 210 mm | 1410 g |
| 24       | 345 mm | 300 mm | 435 mm | 6290 g |



