



# Datasheet | IEC (Coax) CAT6 Combi

## RG58 | 75 Ohm | Triple Shielded | ECA | 25.0 m | Round | White | Gift Box

Brand: Nedis | Article number: CSGG4500WT250 | Product EAN number: 5412810320318

### Product specifications

|                               |                 |
|-------------------------------|-----------------|
| Cable design                  | Round           |
| Cable length                  | 25.0 m          |
| Cable mantle material         | PVC             |
| Cable mantle size             | 10.4 mm         |
| Cable type                    | Coax / Cat6     |
| Coax type                     | RG58            |
| Colour                        | White           |
| Conductor diameter            | 0.58 mm         |
| Conductor material            | OFC             |
| CPR class                     | ECA             |
| Dielectric diameter           | 2.6 mm          |
| Frequency                     | 250 MHz         |
| Impedance                     | 75 Ohm          |
| Insulation material           | PE              |
| Material                      | PVC             |
| Maximum bandwidth             | 1 Gbps          |
| Number of products in package | 1 pcs           |
| Packaging                     | Gift Box        |
| Shielding                     | Triple Shielded |

### Packaging information

|                     |                                  |
|---------------------|----------------------------------|
| Brand               | Nedis                            |
| Order code          | CSGG4500WT250                    |
| EAN single product: | 5412810320318                    |
| EAN Inner carton:   |                                  |
| EAN Outer carton:   | 5412810464470                    |
| Packaging           | Giftbox                          |
| Package contents    | 1x Coax / CAT6 Combination Cable |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 105 mm | 230 mm | 230 mm | 2130 g  |
| 4        | 240 mm | 240 mm | 420 mm | 8860 g  |
| 8        | 270 mm | 445 mm | 495 mm | 16020 g |

