


LNB | Single | Output connection: 1x F-Connector | Noise figure range: 0.90 dB | Conversion gain: 53 - 65 dB | White



Product specifications SLNB10SWT:

Colour	White	Number of products in package	1 pcs
Conversion gain	53 - 65 dB	Operating temperature range	-40 - 70 °C
Cross polarization	18 dB	Output connection	1x F-Connector
Current consumption	0.08 A	Output frequency range high band	1.100 - 2.150 GHz
Gain flatness 26 MHz bandwidth	± 0,5 dB	Output spurious	-60 dB
High band switching	22 kHz	Polarity switching voltage horizontal	DC 16.0 - 20.0 V
Image rejection (min.)	40 dB	Polarity switching voltage vertical	DC 11.0 - 14.0 V
Input frequency range high band	11.7 - 12.75 GHz	Satellite accessory type	LNB
Input frequency range low band	10.7 - 11.7 GHz		
LNB type	Single		
Local oscillator frequency phase noise	-80 dB c/Hz @ 10 kHz (max.)		
Low band switching	0 kHz		
Material	ABS		
	Metal		
Noise figure range	0.90 dB		

Packaging information:

Brand	Nedis
Order code	SLNB10SWT
EAN single Product	5412810320806
EAN Inner Carton	
EAN Outer Carton	5412810384839
Packaging	Giftbox
Package contents	LNB

Quantity	L x	W x	H (mm)	Weight
1	65 mm	105 mm	65 mm	104 g
135	340 mm	335 mm	575 mm	14820 g

