

# Datasheet | Coax Cable

**IEC (Coax) Male | IEC (Coax) Female | Gold Plated | 100 dB | 75 Ohm | Double Shielded | 1.00 m | Round | PVC | White | Box**

Brand: Nedis | Article number: CSBW40015WT10 | Product EAN number: 5412810326365

## Product specifications

|                               |                   |
|-------------------------------|-------------------|
| Cable design                  | Round             |
| Cable length                  | 1.00 m            |
| Cable mantle material         | PVC               |
| Cable mantle size             | 5.0 mm            |
| Cable type                    | Coax              |
| Colour                        | White             |
| Conductor diameter            | 0.50 mm           |
| Conductor material            | Bare Copper       |
| Connector A                   | IEC (Coax) Male   |
| Connector B                   | IEC (Coax) Female |
| Connector design - side A     | Straight          |
| Connector design - side B     | Straight          |
| Connector material            | PVC               |
| Connector plating             | Gold Plated       |
| Dielectric diameter           | 3.1 mm            |
| Impedance                     | 75 Ohm            |
| Insulation material           | PE                |
| Material                      | Metal             |
|                               | PVC               |
| Number of products in package | 1 pcs             |
| Packaging                     | Box               |
| Shielding                     | Double Shielded   |
| Signal to Noise Ratio         | 100 dB            |

## Packaging information

|                     |               |
|---------------------|---------------|
| Brand               | Nedis         |
| Order code          | CSBW40015WT10 |
| EAN single product: | 5412810326365 |
| EAN Inner carton:   | 5412810392513 |
| EAN Outer carton:   | 5412810369287 |
| Packaging           | Box           |
| Package contents    |               |

| Quantity | L x    | W x    | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1        | 25 mm  | 235 mm | 60 mm  | 68 g   |
| 10       | 70 mm  | 250 mm | 225 mm | 730 g  |
| 60       | 230 mm | 285 mm | 465 mm | 4860 g |

