

Datasheet | Coax Cable

IEC (Coax) Male | IEC (Coax) Female | Gold Plated | 100 dB | 75 Ohm | Double Shielded | 3.00 m | Round | PVC | White | Box

Brand: Nedis | Article number: CSBW40015WT30 | Product EAN number: 5412810326372

Product specifications Cable design Round Cable length 3.00 m Cable mantle material PVC Cable mantle size 5.0 mm Cable type Coax Colour White Conductor diameter 0.50 mm Conductor material Bare Copper Connector A IEC (Coax) Male Connector B IEC (Coax) Female Connector design - side A Straight Connector material PVC Connector plating Gold Plated Dielectric diameter 3.1 mm Impedance 75 Ohm Insulation material PE Material Metal PVC Number of products in package 1 pcs Packaging Box	
Cable length Cable mantle material PVC Cable mantle size Cable type Coax Colour White Conductor diameter Conductor material Bare Copper Connector A IEC (Coax) Male Connector B Connector design - side A Connector design - side B Straight Connector plating Dielectric diameter Insulation material Metal PVC Number of products in package 3.00 m 3.00 m 3.00 m 3.00 m 3.00 m PVC Goax Fonm Goax White Coax UFC (Coax) Male IEC (Coax) Female Straight Straight PVC Gold Plated 3.1 mm PE Metal PVC Number of products in package 1 pcs	
Cable mantle material PVC Cable mantle size S.0 mm Coax Colour White Conductor diameter O.50 mm Conductor material Bare Copper Connector A IEC (Coax) Male Connector B IEC (Coax) Female Connector design - side A Straight Connector material PVC Connector plating Dielectric diameter Impedance Insulation material Metal PVC Number of products in package 5.0 mm PVC Toax Straight PVC Tobal Plated T	
Cable mantle size Cable type Coax Colour White Conductor diameter Conductor material Bare Copper Connector A IEC (Coax) Male Connector B Connector design - side A Connector design - side B Connector material PVC Connector plating Dielectric diameter Impedance Insulation material Metal PVC Number of products in package 5.0 mm IEC (Coax) Female Bare Copper IEC (Coax) Female Straight Straight Straight PVC Straight PVC All mm Impedance T5 Ohm Insulation material PE Metal PVC Number of products in package 1 pcs	
Cable type Coax Colour White Conductor diameter Conductor material Bare Copper Connector A IEC (Coax) Male Connector B IEC (Coax) Female Connector design - side A Connector design - side B Connector material Connector plating Connector plating Dielectric diameter Insulation material Metal Metal PVC Number of products in package Coox Mhite Moss Gold Plated 3.1 mm Metal PVC Number of products in package 1 pcs	
Colour White Conductor diameter Conductor material Connector A IEC (Coax) Male IEC (Coax) Female Connector design - side A Connector design - side B Connector material Connector plating Dielectric diameter Impedance Impedance Impedance Impedance Impedance Impedance Impedance Impedance Insulation material Insulation material Impedance Insulation material Insul	า
Conductor diameter Conductor material Bare Copper Connector A Connector B Connector design - side A Connector design - side B Connector material Connector plating Dielectric diameter Impedance Impedance Material Metal PVC Number of products in package O.50 mm IEC (Coax) Male IEC (Coax) Female Straight Straight Straight Oold Plated 3.1 mm 75 Ohm PE Metal PVC 1 pcs	
Conductor material Connector A IEC (Coax) Male IEC (Coax) Female Connector design - side A Connector design - side B Connector material Connector plating Dielectric diameter Impedance Insulation material PE Material Metal PVC Number of products in package IEC (Coax) Female Straight Straight Connector design - side B Straight PVC Gold Plated 3.1 mm PE Metal PVC 1 pcs	
Connector A Connector B IEC (Coax) Male IEC (Coax) Female Connector design - side A Connector design - side B Connector material PVC Connector plating Dielectric diameter Impedance Insulation material PE Material Metal PVC Number of products in package IEC (Coax) Male IEC (Coax) Female Straight PVC 1 pcs	m
Connector B Connector design - side A Connector design - side B Connector material Connector plating Dielectric diameter Impedance Impedance Material Metal PVC Number of products in package IEC (Coax) Female Straight Conax Gemale Straight PVC Straight Straight PVC Straight PVC Straight Straight PVC Straight Straight PVC Straight Straight PVC Straight Straight PVC Straight P	opper
Connector design - side A Connector design - side B Connector material Connector plating Dielectric diameter Impedance Insulation material Metal PVC Number of products in package Straight Straight Straight Connector plating Gold Plated 3.1 mm 75 Ohm PE Metal PVC	ax) Male
Connector design - side B Connector material PVC Connector plating Dielectric diameter Impedance Insulation material Metal PVC Number of products in package Straight Straight Straight PVC All Material Straight PVC All Metal PVC 1 pcs	ax) Female
Connector material PVC Connector plating Gold Plated Dielectric diameter 3.1 mm Impedance 75 Ohm Insulation material PE Material Metal PVC Number of products in package 1 pcs	it
Connector plating Gold Plated Dielectric diameter 3.1 mm Impedance 75 Ohm Insulation material PE Material Metal PVC Number of products in package 1 pcs	it
Dielectric diameter 3.1 mm Impedance 75 0hm Insulation material PE Material Metal PVC Number of products in package 1 pcs	
Impedance 75 Ohm Insulation material PE Material Metal PVC Number of products in package 1 pcs	ated
Insulation material PE Material Metal PVC Number of products in package 1 pcs	1
Material Metal PVC Number of products in package 1 pcs	n
PVC Number of products in package 1 pcs	
Number of products in package 1 pcs	
Packaging Roy	
T deltaging	
Shielding Double Shielded	Shielded
Siliciding Bodble Silicided	1
Silicianis	

Packaging information	on
Brand	Nedis
Order code	CSBW40015WT30
EAN single product:	5412810326372
EAN Inner carton:	5412810392544
EAN Outer carton:	5412810369317
Packaging	Вох
Package contents	

Quantity	Lx	Wx	H (mm)	Weight
1	30 mm	230 mm	80 mm	126 g
10	100 mm	250 mm	330 mm	1375 g
40	355 mm	280 mm	400 mm	6240 g





