


Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Gold Plated | 100 dB | 75 Ohm | Double Shielded | 10.0 m | Round | PVC | White | Box



Product specifications CSBW40015WT100:

| | | | |
|---------------------------|-------------------|-------------------------------|-----------------|
| Cable design | Round | Insulation material | PE |
| Cable length | 10.0 m | Material | Metal |
| Cable mantle material | PVC | | PVC |
| Cable mantle size | 5.0 mm | Number of products in package | 1 pcs |
| Cable type | Coax | Packaging | Box |
| Colour | White | Shielding | Double Shielded |
| Conductor diameter | 0.50 mm | Signal to Noise Ratio | 100 dB |
| Conductor material | Bare Copper | | |
| Connector A | IEC (Coax) Male | | |
| Connector B | IEC (Coax) Female | | |
| Connector design - side A | Straight | | |
| Connector design - side B | Straight | | |
| Connector material | PVC | | |
| Connector plating | Gold Plated | | |
| Dielectric diameter | 3.1 mm | | |
| Impedance | 75 Ohm | | |

Packaging information:

| | |
|--------------------|----------------|
| Brand | Nedis |
| Order code | CSBW40015WT100 |
| EAN single Product | 5412810326396 |
| EAN Inner Carton | 5412810392520 |
| EAN Outer Carton | 5412810369294 |
| Packaging | Box |
| Package contents | |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 65 mm | 235 mm | 130 mm | 344 g |
| 5 | 250 mm | 155 mm | 320 mm | 1900 g |
| 20 | 340 mm | 335 mm | 505 mm | 8460 g |

