

F Quick - F Quick Cables | F Male Quick | F Male Quick | Gold Plated | 75 Ohm | Double Shielded | 5.00 m | Round | PVC | White | Window Box



Product specifications CSBW41300WT50:

| | | | |
|---------------------------|--------------|-------------------------------|-----------------|
| Cable design | Round | | PVC |
| Cable length | 5.00 m | Number of products in package | 1 pcs |
| Cable mantle material | PVC | Packaging | Window Box |
| Cable mantle size | 5.0 mm | Shielding | Double Shielded |
| Cable type | F | | |
| Colour | White | | |
| Conductor diameter | 0.50 mm | | |
| Conductor material | Copper | | |
| Connector A | F Male Quick | | |
| Connector B | F Male Quick | | |
| Connector design - side A | Straight | | |
| Connector design - side B | Straight | | |
| Connector material | Zinc | | |
| Connector plating | Gold Plated | | |
| Dielectric diameter | 3.1 mm | | |
| Impedance | 75 Ohm | | |
| Insulation material | PE | | |
| Material | Metal | | |

Packaging information:

| | |
|--------------------|---------------|
| Brand | Nedis |
| Order code | CSBW41300WT50 |
| EAN single Product | 5412810326440 |
| EAN Inner Carton | 5412810392742 |
| EAN Outer Carton | 5412810369515 |
| Packaging | |
| Package contents | |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 85 mm | 50 mm | 230 mm | 220 g |
| 5 | 255 mm | 90 mm | 265 mm | 1160 g |
| 30 | 300 mm | 280 mm | 525 mm | 7680 g |

