Datasheet | LED Batten Light | BTTNT812W60

LED Batten Light | 600 mm | 1320 lm | 4000 K | 12 W | IP65



Product specifications BTTNT812W60:

Adjustment possibilities	Not adjustable		
Beam angle	125 °		
Body material	Polycarbonate		
Colour	White		
Colour consistency (SDCM)	≤ 6		
Colour rendering index (Ra)	≥ 80		
Colour temperature	4000 K		
Dimmable	No		
Energy class	Е		
Energy consumption per 1000 hours	11 kWh		
EPREL ID	943674		
Especially for bathroom	No		
Indoor / outdoor	Indoor		
Input voltage	220 - 240 V AC 50/60 Hz		
Interconnactable	Yes, per type		
IP rating	IP65		

Lamp finish	Clear		
Lamp included	Integrated		
Length	600 mm		
Light colour	Cool White		
Lighting control	Wall Switch		
Lumen maintenance factor	70.0 %		
Material	Polycarbonate		
Maximum power consumption	11 W		
Motion sensor	No		
Number of products in package	1 pcs		
Number of switching cycles	≥ 20000 Switching Cycles		
Operating temperature range	-20 - 50 °C		
Place of lighting	Ceiling		
	Wall		
Power factor	≥ 0.9		
Power source type	Mains Powered		

Rated life time of lamp	25000 h
Rated luminous flux	1320 lm
Rated peak intensity in candela	N/A
Starting time	0.5s
Technology	LED
Warm-up time to 60% light	Instant Full Light (1 s)
Wattage	12 W
Wattage equivalent	75 W

Packaging information:

Brand	Nedis
Order code	BTTNT8-12W60
EAN single Product	5412810336999
EAN Inner Carton	
EAN Outer Carton	
Packaging	Wrap
Package contents	Batten fixture
	Mounting materials

Read more online

Quantity	Lx	Wx	H (mm)	Weight
1	70 mm	70 mm	655 mm	475 g
6	225 mm	160 mm	665 mm	3300 g

