

Datasheet | LED Batten Light

600 mm | 1320 lm | 4000 K | 12 W | IP65

Brand: Nedis | Article number: BTTNT8-12W60 | Product EAN number: 5412810336999

Product specifications

| | |
|-----------------------------------|---------------------------------|
| Adjustment possibilities | Not adjustable |
| Beam angle | 125 ° |
| Body material | Polycarbonate |
| Colour | White |
| Colour consistency (SDCM) | ≤ 6 |
| Colour rendering index (Ra) | ≥ 80 |
| Colour temperature | 4000 K |
| Dimmable | No |
| Energy class | E |
| Energy consumption per 1000 hours | 11 kWh |
| EPREL ID | 943674 |
| Especially for bathroom | No |
| Indoor / outdoor | Indoor |
| Input voltage | 220 - 240 V AC 50/60 Hz |
| Interconnectable | Yes, per type |
| IP rating | IP65 |
| Lamp finish | Clear |
| Lamp included | Integrated |
| Length | 600 mm |
| Light colour | Cool White |
| Lighting control | Wall Switch |
| Lumen maintenance factor | 70.0 % |
| Material | Polycarbonate |
| Maximum power consumption | 11 W |
| Motion sensor | No |
| Number of products in package | 1 pcs |
| Number of switching cycles | ≥ 20000 Switching Cycles |
| Operating temperature range | -20 - 50 °C |
| Place of lighting | Ceiling |
| | Wall |
| Power factor | ≥ 0.9 |
| Power source type | Mains Powered |
| Rated life time of lamp | 25000 h |
| Rated luminous flux | 1320 lm |

| | |
|---------------------------------|---------------------------------|
| Rated peak intensity in candela | N/A |
| Starting time | 0.5s |
| Technology | LED |
| Warm-up time to 60% light | Instant Full Light (1 s) |
| Wattage | 12 W |
| Wattage equivalent | 75 W |

Packaging information

| | |
|---------------------|---------------------------|
| Brand | Nedis |
| Order code | BTTNT8-12W60 |
| EAN single product: | 5412810336999 |
| EAN Inner carton: | |
| EAN Outer carton: | |
| Packaging | Wrap |
| Package contents | Batten fixture |
| | Mounting materials |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 70 mm | 70 mm | 655 mm | 475 g |
| 6 | 225 mm | 160 mm | 665 mm | 3300 g |

