

LED Batten Light | 1200 mm | 5000 lm | 4000 K | 44 W | IP65



Product specifications BTTNT844W120:

Adjustment possibilities	Not adjustable	Lamp finish	Clear	Rated life time of lamp	25000 h
Beam angle	125 °	Lamp included	Integrated	Rated luminous flux	5000 lm
Body material	Polycarbonate	Length	1200 mm	Rated peak intensity in candela	N/A
Colour	White	Light colour	Cool White	Starting time	0.5s
Colour consistency (SDCM)	≤ 6	Lighting control	Wall Switch	Technology	LED
Colour rendering index (Ra)	≥ 80	Lumen maintenance factor	70.0 %	Warm-up time to 60% light	Instant Full Light (1 s)
Colour temperature	4000 K	Material	Polycarbonate	Wattage	44 W
Dimmable	No	Maximum power consumption	43 W	Wattage equivalent	247 W
Energy class	E	Motion sensor	No		
Energy consumption per 1000 hours	43 kWh	Number of products in package	1 pcs		
EPREL ID	943721	Number of switching cycles	≥ 20000 Switching Cycles		
Especially for bathroom	No	Operating temperature range	-20 - 50 °C		
Indoor / outdoor	Indoor	Place of lighting	Ceiling		
Input voltage	220 - 240 V AC		Wall		
	50/60 Hz	Power factor	≥ 0.9		
Interconnectable	Yes, per type	Power source type	Mains Powered		
IP rating	IP65				

Packaging information:

Brand	Nedis
Order code	BTTNT8-44W120
EAN single Product	5412810337033
EAN Inner Carton	
EAN Outer Carton	5412810410712
Packaging	Wrap
Package contents	Batten fixture
	Mounting materials

Read more online

Quantity	L x	W x	H (mm)	Weight
1	90 mm	70 mm	1255 mm	1 g
6	285 mm	170 mm	1265 mm	6600 g

