

**LED Batten Light | 1500 mm | 3150 lm | 4000 K | 28 W | IP65**



**Product specifications BTTNT828W150:**

|                                   |                            |                               |                             |                                 |                          |
|-----------------------------------|----------------------------|-------------------------------|-----------------------------|---------------------------------|--------------------------|
| Adjustment possibilities          | Not adjustable             | Lamp finish                   | Clear                       | Rated life time of lamp         | 25000 h                  |
| Beam angle                        | 125 °                      | Lamp included                 | Integrated                  | Rated luminous flux             | 3150 lm                  |
| Body material                     | Polycarbonate              | Length                        | 1500 mm                     | Rated peak intensity in candela | N/A                      |
| Colour                            | White                      | Light colour                  | Cool White                  | Starting time                   | 0.5s                     |
| Colour consistency (SDCM)         | ≤ 6                        | Lighting control              | Wall Switch                 | Technology                      | LED                      |
| Colour rendering index (Ra)       | ≥ 80                       | Lumen maintenance factor      | 70.0 %                      | Warm-up time to 60% light       | Instant Full Light (1 s) |
| Colour temperature                | 4000 K                     | Material                      | Polycarbonate               | Wattage                         | 28 W                     |
| Dimmable                          | No                         | Maximum power consumption     | 30 W                        | Wattage equivalent              | 162 W                    |
| Energy class                      | E                          | Motion sensor                 | No                          |                                 |                          |
| Energy consumption per 1000 hours | 30 kWh                     | Number of products in package | 1 pcs                       |                                 |                          |
| EPREL ID                          | 943737                     | Number of switching cycles    | ≥ 20000<br>Switching Cycles |                                 |                          |
| Especially for bathroom           | No                         | Operating temperature range   | -20 - 50 °C                 |                                 |                          |
| Indoor / outdoor                  | Indoor                     | Place of lighting             | Ceiling                     |                                 |                          |
| Input voltage                     | 220 - 240 V AC<br>50/60 Hz |                               | Wall                        |                                 |                          |
| Interconnectable                  | Yes, per type              | Power factor                  | ≥ 0.9                       |                                 |                          |
| IP rating                         | IP65                       | Power source type             | Mains Powered               |                                 |                          |

**Packaging information:**

|                    |                                      |
|--------------------|--------------------------------------|
| Brand              | Nedis                                |
| Order code         | BTTNT8-28W150                        |
| EAN single Product | 5412810337040                        |
| EAN Inner Carton   |                                      |
| EAN Outer Carton   | 5412810415199                        |
| Packaging          | Wrap                                 |
| Package contents   | Batten fixture<br>Mounting materials |

**Read more online**

| Quantity | L x   | W x   | H (mm)  | Weight |
|----------|-------|-------|---------|--------|
| 1        | 65 mm | 65 mm | 1550 mm | 920 g  |

