


LED Batten Light | 1500 mm | 6300 lm | 4000 K | 55 W | IP65



Product specifications BTTNT855W150:

Adjustment possibilities	Not adjustable	Lamp finish	Clear	Rated life time of lamp	25000 h
Beam angle	125 °	Lamp included	Integrated	Rated luminous flux	6300 lm
Body material	Polycarbonate	Length	1500 mm	Rated peak intensity in candela	N/A
Colour	White	Light colour	Cool White	Starting time	0.5s
Colour consistency (SDCM)	≤ 6	Lighting control	Wall Switch	Technology	LED
Colour rendering index (Ra)	≥ 80	Lumen maintenance factor	70.0 %	Warm-up time to 60% light	Instant Full Light (1 s)
Colour temperature	4000 K	Material	Polycarbonate	Wattage	55 W
Dimmable	No	Maximum power consumption	60 W	Wattage equivalent	307 W
Energy class	E	Motion sensor	No		
Energy consumption per 1000 hours	60 kWh	Number of products in package	1 pcs		
EPREL ID	943751	Number of switching cycles	≥ 20000 Switching Cycles		
Especially for bathroom	No	Operating temperature range	-20 - 50 °C		
Indoor / outdoor	Indoor	Place of lighting	Ceiling		
Input voltage	220 - 240 V AC 50/60 Hz		Wall		
Interconnectable	Yes, per type	Power factor	≥ 0.9		
IP rating	IP65	Power source type	Mains Powered		

Packaging information:

Brand	Nedis
Order code	BTTNT8-55W150
EAN single Product	5412810337057
EAN Inner Carton	
EAN Outer Carton	5412810410729
Packaging	Wrap
Package contents	Batten fixture Mounting materials

Read more online

Quantity	L x	W x	H (mm)	Weight
1	85 mm	70 mm	1550 mm	1 g
6	1555 mm	160 mm	280 mm	1 g

