

HDMI™ Matrix Switch | 4 x 2 port(s) | 4x HDMI™ Input | 2x 3.5 mm / 2x HDMI™ Output / 2x TosLink | 4K@60Hz | 18 Gbps | Remote controlled | Metal | Anthracite



Product specifications VMAT3482AT:

| | | | | | |
|----------------------------------|-----------------|-------------------------------------|--------------------------|-------------------------------|---------------|
| Bandwidth | 600 mHz | Device type | HDMI™ Matrix Switch | Power source type | Mains Powered |
| Clock frequency | 0 MHz | EDID settings | Auto | Remote controlled | Yes |
| Colour | Anthracite | HDCP version | HDCP 2.2 Compatible | Required batteries (included) | 1x CR2032 |
| Colour formats | RGB | Input current | 2 A | Supported resolutions | 1080i |
| | YCbCr 4:2:0 | Input voltage | 5 V DC | | 1080p |
| | YCbCr 4:2:2 | Material | Metal | | 480i |
| | YCbCr 4:4:4 | Maximum bandwidth | 18 Gbps | | 480p |
| Connection input | 4x HDMI™ Input | Maximum resolution | 4K@60Hz | | 4K@30Hz |
| Connection output | 2x 3.5 mm | Number of products in package | 1 pcs | | 4K@60Hz |
| | 2x HDMI™ Output | Ports | 4 x 2 port(s) | | 576i |
| | 2x TosLink | Power adapter cable length | 1.0 m | | 576p |
| Controlling method | Manual | Power consumption in operating mode | 5 W | Supported technology | 720p |
| | Remote Control | Power consumption in standby mode | 1 W | | ARC |
| Device power input connection(s) | DC 9.0 x 5.5 mm | Power plug | Euro / Type-C (CEE 7/16) | | Dolby Digital |
| | | | | | Dolby True HD |
| | | | | | DTS Digital |
| | | | | | DTS-HD |

Packaging information:

| | |
|--------------------|--|
| Brand | Nedis |
| Order code | VMAT3482AT |
| EAN single Product | 5412810337231 |
| EAN Inner Carton | |
| EAN Outer Carton | 5412810337248 |
| Packaging | Box |
| Package contents | HDMI™ Matrix Power adapter 5 V DC – 2 A |

Read more online

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|---------|
| 1 | 215 mm | 55 mm | 290 mm | 1020 g |
| 10 | 310 mm | 235 mm | 550 mm | 10980 g |

