

USB Cable | USB 2.0 | USB-C™ Male | USB-C™ Male | 240 W | 480 Mbps | Nickel Plated | 2.00 m | Round | PVC | Black | Envelope



Product specifications CCGP60710BK20:

| | | | |
|-------------------------------|---------------|----------------|----------|
| AWG value | 30 | Output power | 240 W |
| Cable design | Round | Packaging | Envelope |
| Cable length | 2.00 m | USB technology | USB 2.0 |
| Cable mantle material | PVC | | |
| Cable mantle size | 4.0 mm | | |
| Cable type | USB 2.0 | | |
| Colour | Black | | |
| Conductor material | Tinned Copper | | |
| Connector A | USB-C™ Male | | |
| Connector B | USB-C™ Male | | |
| Connector design - side A | Straight | | |
| Connector design - side B | Straight | | |
| Connector material | PVC | | |
| Connector plating | Nickel Plated | | |
| Material | PVC | | |
| Maximum transfer rate | 480 Mbps | | |
| Number of products in package | 1 pcs | | |
| Output current | 5.0 A | | |

Packaging information:

| | |
|--------------------|---------------|
| Brand | Nedis |
| Order code | CCGP60710BK20 |
| EAN single Product | 5412810414017 |
| EAN Inner Carton | 5412810414024 |
| EAN Outer Carton | 5412810414031 |
| Packaging | Envelope |
| Package contents | |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 30 mm | 230 mm | 55 mm | 76 g |
| 50 | 290 mm | 245 mm | 310 mm | 4060 g |
| 100 | 340 mm | 315 mm | 510 mm | 8820 g |

