

Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 3.00 m | Round | PVC | White | Label



Product specifications CSGL40000WT30:

| | | | |
|---------------------------|-------------------|-------------------------------|-----------------|
| Cable design | Round | Insulation material | PE |
| Cable length | 3.00 m | Material | PVC |
| Cable mantle material | PVC | Number of products in package | 1 pcs |
| Cable mantle size | 5.0 mm | Packaging | Label |
| Cable type | Coax | Shielding | Double Shielded |
| Colour | White | Signal to Noise Ratio | 90 dB |
| Conductor diameter | 0.50 mm | | |
| Conductor material | CCS | | |
| Connector A | IEC (Coax) Male | | |
| Connector B | IEC (Coax) Female | | |
| Connector design - side A | Straight | | |
| Connector design - side B | Straight | | |
| Connector material | PVC | | |
| Connector plating | Nickel Plated | | |
| Dielectric diameter | 2.7 mm | | |
| Impedance | 75 Ohm | | |

Packaging information:

| | |
|--------------------|--------------------|
| Brand | Nedis |
| Order code | CSGL40000WT30 |
| EAN single Product | 5412810425778 |
| EAN Inner Carton | 5412810431724 |
| EAN Outer Carton | 5412810437184 |
| Packaging | Label |
| Package contents | 1x Coax Cable 90dB |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|---------|
| 1 | 160 mm | 190 mm | 20 mm | 90 g |
| 40 | 265 mm | 230 mm | 270 mm | 3680 g |
| 160 | 290 mm | 475 mm | 560 mm | 15380 g |

