


**Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 1.50 m | Round | PVC | White | Label**



**Product specifications CSGL40020WT15:**

Cable design	Round	Insulation material	PE
Cable length	1.50 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	6.0 mm	Packaging	Label
Cable type	Coax	Shielding	Quad Shielded
Colour	White	Signal to Noise Ratio	120 dB
Conductor diameter	0.50 mm		
Conductor material	OFC		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	3.1 mm		
Impedance	75 Ohm		

**Packaging information:**

Brand	Nedis
Order code	CSGL40020WT15
EAN single Product	5412810425815
EAN Inner Carton	5412810440696
EAN Outer Carton	5412810440702
Packaging	Label
Package contents	1x Coax Cable 120dB

Quantity	L x	W x	H (mm)	Weight
1	155 mm	220 mm	25 mm	90 g
50	325 mm	165 mm	450 mm	5020 g
100	345 mm	360 mm	470 mm	10800 g

