

## IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 15.0 m | Round | PVC | White | Label

Brand: Nedis | Article number: CSG40020WT150 | Product EAN number: 5412810425822

### Product specifications

|                               |                   |
|-------------------------------|-------------------|
| Cable design                  | Round             |
| Cable length                  | 15.0 m            |
| Cable mantle material         | PVC               |
| Cable mantle size             | 6.0 mm            |
| Cable type                    | Coax              |
| Colour                        | White             |
| Conductor diameter            | 0.50 mm           |
| Conductor material            | OFC               |
| Connector A                   | IEC (Coax) Male   |
| Connector B                   | IEC (Coax) Female |
| Connector design - side A     | Straight          |
| Connector design - side B     | Straight          |
| Connector material            | PVC               |
| Connector plating             | Nickel Plated     |
| Dielectric diameter           | 3.1 mm            |
| Impedance                     | 75 Ohm            |
| Insulation material           | PE                |
| Material                      | PVC               |
| Number of products in package | 1 pcs             |
| Packaging                     | Label             |
| Shielding                     | Quad Shielded     |
| Signal to Noise Ratio         | 120 dB            |

### Packaging information

|                     |                     |
|---------------------|---------------------|
| Brand               | Nedis               |
| Order code          | CSGL40020WT150      |
| EAN single product: | 5412810425822       |
| EAN Inner carton:   | 5412810442218       |
| EAN Outer carton:   | 5412810442225       |
| Packaging           | Label               |
| Package contents    | 1x Coax Cable 120dB |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 145 mm | 210 mm | 85 mm  | 622 g   |
| 10       | 165 mm | 420 mm | 295 mm | 6500 g  |
| 20       | 320 mm | 450 mm | 350 mm | 13640 g |

