


**Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 2.00 m | Round | PVC | White | Label**



**Product specifications CSGL40020WT20:**

Cable design	Round	Insulation material	PE
Cable length	2.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	6.0 mm	Packaging	Label
Cable type	Coax	Shielding	Quad Shielded
Colour	White	Signal to Noise Ratio	120 dB
Conductor diameter	0.50 mm		
Conductor material	OFC		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	3.1 mm		
Impedance	75 Ohm		

**Packaging information:**

Brand	Nedis
Order code	CSGL40020WT20
EAN single Product	5412810425839
EAN Inner Carton	5412810442232
EAN Outer Carton	5412810442249
Packaging	Label
Package contents	1x Coax Cable 120dB

Quantity	L x	W x	H (mm)	Weight
1	25 mm	220 mm	140 mm	111 g
50	310 mm	210 mm	420 mm	6100 g
100	325 mm	440 mm	435 mm	12600 g

