

# Datasheet | Coax Cable

**IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 3.00 m | Round | PVC | Black | Label**

Brand: Nedis | Article number: CSG40120BK30 | Product EAN number: 5412810425877

## Product specifications

|                               |                   |
|-------------------------------|-------------------|
| Cable design                  | Round             |
| Cable length                  | 3.00 m            |
| Cable mantle material         | PVC               |
| Cable mantle size             | 6.0 mm            |
| Cable type                    | Coax              |
| Colour                        | Black             |
| Conductor diameter            | 0.50 mm           |
| Conductor material            | OFC               |
| Connector A                   | IEC (Coax) Male   |
| Connector B                   | IEC (Coax) Female |
| Connector design - side A     | Angled 90°        |
| Connector design - side B     | Angled 90°        |
| Connector material            | PVC               |
| Connector plating             | Nickel Plated     |
| Dielectric diameter           | 3.1 mm            |
| Impedance                     | 75 Ohm            |
| Insulation material           | PE                |
| Material                      | PVC               |
| Number of products in package | 1 pcs             |
| Packaging                     | Label             |
| Shielding                     | Quad Shielded     |
| Signal to Noise Ratio         | 120 dB            |

## Packaging information

|                     |                     |
|---------------------|---------------------|
| Brand               | Nedis               |
| Order code          | CSGL40120BK30       |
| EAN single product: | 5412810425877       |
| EAN Inner carton:   | 5412810442133       |
| EAN Outer carton:   | 5412810442140       |
| Packaging           | Label               |
| Package contents    | 1x Coax Cable 120dB |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 25 mm  | 220 mm | 155 mm | 150 g   |
| 50       | 325 mm | 240 mm | 470 mm | 7940 g  |
| 100      | 340 mm | 505 mm | 485 mm | 17480 g |

