


**Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 10.0 m | Round | PVC | White | Box**



**Product specifications CSGB40120WT100:**

Cable design	Round	Insulation material	PE
Cable length	10.0 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	6.0 mm	Packaging	Box
Cable type	Coax	Shielding	Quad Shielded
Colour	White	Signal to Noise Ratio	120 dB
Conductor diameter	0.50 mm		
Conductor material	OFC		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Angled 90°		
Connector design - side B	Angled 90°		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	3.1 mm		
Impedance	75 Ohm		

**Packaging information:**

Brand	Nedis
Order code	CSGB40120WT100
EAN single Product	5412810425891
EAN Inner Carton	5412810439997
EAN Outer Carton	5412810440009
Packaging	Box
Package contents	1x Coax Cable 120dB

Quantity	L x	W x	H (mm)	Weight
1	130 mm	235 mm	60 mm	452 g
5	150 mm	255 mm	325 mm	2455 g
20	320 mm	355 mm	550 mm	10720 g

