

Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 1.50 m | Round | PVC | White | Box



Product specifications CSGB40120WT15:

| | | | |
|---------------------------|-------------------|-------------------------------|---------------|
| Cable design | Round | Insulation material | PE |
| Cable length | 1.50 m | Material | PVC |
| Cable mantle material | PVC | Number of products in package | 1 pcs |
| Cable mantle size | 6.0 mm | Packaging | Box |
| Cable type | Coax | Shielding | Quad Shielded |
| Colour | White | Signal to Noise Ratio | 120 dB |
| Conductor diameter | 0.50 mm | | |
| Conductor material | OFC | | |
| Connector A | IEC (Coax) Male | | |
| Connector B | IEC (Coax) Female | | |
| Connector design - side A | Angled 90° | | |
| Connector design - side B | Angled 90° | | |
| Connector material | PVC | | |
| Connector plating | Nickel Plated | | |
| Dielectric diameter | 3.1 mm | | |
| Impedance | 75 Ohm | | |

Packaging information:

| | |
|--------------------|---------------------|
| Brand | Nedis |
| Order code | CSGB40120WT15 |
| EAN single Product | 5412810425914 |
| EAN Inner Carton | 5412810440016 |
| EAN Outer Carton | 5412810440023 |
| Packaging | Box |
| Package contents | 1x Coax Cable 120dB |

| Quantity | L x | W x | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 35 mm | 230 mm | 55 mm | 107 g |
| 10 | 250 mm | 85 mm | 335 mm | 1284 g |
| 60 | 360 mm | 270 mm | 515 mm | 8640 g |

