

Coax Cable | IEC (Coax) Male | IEC (Coax) Male | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 3.00 m | Round | PVC | White | Label



Product specifications CSGL40200WT30:

Cable design	Round	Insulation material	PE
Cable length	3.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	5.0 mm	Packaging	Label
Cable type	Coax	Shielding	Double Shielded
Colour	White	Signal to Noise Ratio	90 dB
Conductor diameter	0.50 mm		
Conductor material	CCS		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Male		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	2.7 mm		
Impedance	75 Ohm		

Packaging information:

Brand	Nedis
Order code	CSGL40200WT30
EAN single Product	5412810426003
EAN Inner Carton	5412810431786
EAN Outer Carton	5412810437245
Packaging	Label
Package contents	1x Coax Cable 90dB

Quantity	L x	W x	H (mm)	Weight
1	130 mm	190 mm	30 mm	86 g
40	275 mm	235 mm	275 mm	3600 g
160	290 mm	480 mm	550 mm	15180 g

