



# Datasheet | Coax Cable

## IEC (Coax) Male | IEC (Coax) Male | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 3.00 m | Round | PVC | White | Label

Brand: Nedis | Article number: CSGL40200WT30 | Product EAN number: 5412810426003

### Product specifications

|                               |                 |
|-------------------------------|-----------------|
| Cable design                  | Round           |
| Cable length                  | 3.00 m          |
| Cable mantle material         | PVC             |
| Cable mantle size             | 5.0 mm          |
| Cable type                    | Coax            |
| Colour                        | White           |
| Conductor diameter            | 0.50 mm         |
| Conductor material            | CCS             |
| Connector A                   | IEC (Coax) Male |
| Connector B                   | IEC (Coax) Male |
| Connector design - side A     | Straight        |
| Connector design - side B     | Straight        |
| Connector material            | PVC             |
| Connector plating             | Nickel Plated   |
| Dielectric diameter           | 2.7 mm          |
| Impedance                     | 75 Ohm          |
| Insulation material           | PE              |
| Material                      | PVC             |
| Number of products in package | 1 pcs           |
| Packaging                     | Label           |
| Shielding                     | Double Shielded |
| Signal to Noise Ratio         | 90 dB           |

### Packaging information

|                     |                    |
|---------------------|--------------------|
| Brand               | Nedis              |
| Order code          | CSGL40200WT30      |
| EAN single product: | 5412810426003      |
| EAN Inner carton:   | 5412810431786      |
| EAN Outer carton:   | 5412810437245      |
| Packaging           | Label              |
| Package contents    | 1x Coax Cable 90dB |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 130 mm | 190 mm | 30 mm  | 86 g    |
| 40       | 275 mm | 235 mm | 275 mm | 3600 g  |
| 160      | 290 mm | 480 mm | 550 mm | 15180 g |

