Hirschmann Datasheet | FEKAB5 4G proof IEC

Brand: Hirschmann | Article number: FEKAB5 150 cm shop | Product EAN number: 4002044193270

| Product specifications | |
|-------------------------------|-------------------|
| Cable design | Round |
| Cable length | 1.50 m |
| Cable mantle material | PVC |
| Cable mantle size | 6.9 mm |
| Cable type | Coax |
| Colour | White |
| Conductor diameter | 1.13 mm |
| Conductor material | Bare Copper |
| Connector A | IEC (Coax) Male |
| Connector B | IEC (Coax) Female |
| Connector design - side A | Angled |
| Connector design - side B | Angled |
| Connector material | PVC |
| Connector plating | Nickel Plated |
| Dielectric diameter | 4.8 mm |
| Frequency range | 5 - 3000 MHz |
| Impedance | 75 Ohm |
| Insulation material | PE |
| Number of products in package | 1 pcs |
| Operating temperature range | -30 - 70 °C |
| Packaging | Gift Box |
| Shielding | Triple Shielded |
| Storage temperature | 0 - 60 °C |

| Packaging information | | | | |
|-----------------------|-----------------------|--|--|--|
| Brand | Hirschmann | | | |
| Order code | 695020509 | | | |
| EAN single product: | 4002044193270 | | | |
| EAN Inner carton: | | | | |
| EAN Outer carton: | | | | |
| Packaging | Giftbox with eurolock | | | |
| Package contents | | | | |

| Quantity | Lx | Wx | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1 | 55 mm | 240 mm | 155 mm | 184 g |
| 20 | 360 mm | 295 mm | 425 mm | 4100 g |





