

Datasheet | Fully Wireless

Bluetooth® | Battery play time: 24 hrs | Touch Control | Charging case | Wireless charging case | Built-in microphone | Voice control support | Noise canceling | IPX4 | White

Brand: Nedis | Article number: HPBT2425WT | Product EAN number: 5412810450398

Product specifications			
Battery cable capacity	40 mAh		
Battery play time	24 hrs		
Bluetooth® signal range	10 m		
Bluetooth® version	5.4		
Built-in microphone	Yes		
Charging case	Yes		
Charging case battery capacity	450 mAh		
Charging case battery type	Built-In Lithium- Polymer		
Colour	White		
Control button type	Touch Control		
Device power input connection(s)	USB-C™		
Driver size	10 mm		
Ear hooks	No		
Ear tip sizes included	2x L		
	2x M		
	2x S		
Ear wings	No		
Earphones battery capacity	40 mAh		
Earphones battery play time	6		
Earphones battery type	Built-In Lithium- Polymer		
Frequency response	20 Hz - 20 KHz		
Headphones type	In-Ear		
Impedance	32 Ohm		
Input current	0.35 A		
	5 V DC		
Input voltage	5 V DC		
Input voltage IP rating	5 V DC IPX4		
· -			
IP rating	IPX4		
IP rating Material	IPX4 ABS		
IP rating Material Maximum battery charging time	IPX4 ABS 2 hrs		
IP rating Material Maximum battery charging time Maximum standby time	IPX4 ABS 2 hrs 100 hrs		
IP rating Material Maximum battery charging time Maximum standby time Maximum transmit antenna gain	IPX4 ABS 2 hrs 100 hrs 0 dBi		
IP rating Material Maximum battery charging time Maximum standby time Maximum transmit antenna gain Maximum transmit power	IPX4 ABS 2 hrs 100 hrs 0 dBi 6 dBm		

Power cable length	0.20 m
Power cable side A	USB-C™
Power cable side B	USB-A
Power plug	USB
Power source type	Battery Powered
Rechargeable	Yes
Signal to Noise Ratio	85 dB

Packaging information				
Brand	Nedis			
Order code	HPBT2425WT			
EAN single product:	5412810450398			
EAN Inner carton:	5412810453108			
EAN Outer carton:	5412810453115			
Packaging	Вох			
Package contents	Wireless earphones			
	Charging case			

Quantity	Lx	Wx	H (mm)	Weight
1	30 mm	145 mm	80 mm	94 g
6	95 mm	165 mm	205 mm	619 g
24	230 mm	190 mm	415 mm	2800 g





