

# Neutrik

## Datasheet | 3 pole male

Brand: Neutrik | Article number: NC3MP | Product EAN number:

### Product specifications

|                               |                      |
|-------------------------------|----------------------|
| Colour                        | <b>Silver</b>        |
| Connector design              | <b>Straight</b>      |
| Connector housing material    | <b>Metal</b>         |
| Connector plating             | <b>Nickel Plated</b> |
| Connector type                | <b>XLR 3-Pin</b>     |
| Current                       | <b>16 A</b>          |
| Gender of contacts            | <b>Male</b>          |
| IP rating                     | <b>IP40</b>          |
| Material                      | <b>Metal</b>         |
| Number of products in package | <b>1 pcs</b>         |
| Packaging                     | <b>Polybag</b>       |
| SmartLife                     | <b>No</b>            |
| Temperature range             | <b>-30 - 80 °C</b>   |

### Packaging information

|                     |                  |
|---------------------|------------------|
| Brand               | <b>Neutrik</b>   |
| Order code          | <b>NTR-NC3MP</b> |
| EAN single product: |                  |
| EAN Inner carton:   |                  |
| EAN Outer carton:   |                  |
| Packaging           | <b>Polybag</b>   |
| Package contents    |                  |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 25 mm  | 20 mm  | 25 mm  | 20 g    |
| 20       | 185 mm | 35 mm  | 270 mm | 525 g   |
| 100      | 195 mm | 205 mm | 280 mm | 2780 g  |
| 500      | 400 mm | 200 mm | 500 mm | 12820 g |

