



# Datasheet | CAT5e Network Cable

## U/UTP | RJ45 Male | RJ45 Male | 10.0 m | Round | LSZH | Anthracite | Window Box

Brand: Nedis | Article number: CCBW85100AT100 | Product EAN number: 5412810264001

### Product specifications

|                               |             |
|-------------------------------|-------------|
| AWG value                     | 26          |
| Cable design                  | Round       |
| Cable length                  | 10.0 m      |
| Cable mantle material         | LSZH        |
| Cable mantle size             | 5.0 mm      |
| Cable type                    | CAT5e       |
| Colour                        | Anthracite  |
| Conductor material            | Copper      |
| Connector A                   | RJ45 Male   |
| Connector B                   | RJ45 Male   |
| Connector design - side A     | Straight    |
| Connector design - side B     | Straight    |
| Connector plating             | Gold Plated |
| Frequency                     | 100 MHz     |
| Material                      | PVC         |
| Maximum bandwidth             | 1 Gbps      |
| Number of products in package | 1 pcs       |
| Packaging                     | Window Box  |
| Shielding                     | U/UTP       |
| SmartLife                     | No          |
| Snagless                      | No          |
| Version                       | 1:1         |

### Packaging information

|                     |                         |
|---------------------|-------------------------|
| Brand               | Nedis                   |
| Order code          | CCBW85100AT100          |
| EAN single product: | 5412810264001           |
| EAN Inner carton:   | 5412810391332           |
| EAN Outer carton:   | 5412810364817           |
| Packaging           | Box                     |
| Package contents    | UTP CAT5e network cable |

| Quantity | L x    | W x    | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1        | 50 mm  | 225 mm | 175 mm | 355 g  |
| 5        | 195 mm | 245 mm | 275 mm | 1950 g |
| 20       | 300 mm | 415 mm | 500 mm | 8560 g |

