

## IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 90 dB | 75 Ohm | Double Shielded | 1.50 m | Round | PVC | White | Envelope

Brand: Nedis | Article number: CSGP40000WT15 | Product EAN number: 5412810281848

### Product specifications

|                               |                   |
|-------------------------------|-------------------|
| Cable design                  | Round             |
| Cable length                  | 1.50 m            |
| Cable mantle material         | PVC               |
| Cable mantle size             | 5.0 mm            |
| Cable type                    | Coax              |
| Colour                        | White             |
| Conductor diameter            | 0.50 mm           |
| Conductor material            | CCS               |
| Connector A                   | IEC (Coax) Male   |
| Connector B                   | IEC (Coax) Female |
| Connector design - side A     | Straight          |
| Connector design - side B     | Straight          |
| Connector material            | PVC               |
| Connector plating             | Nickel Plated     |
| Dielectric diameter           | 2.7 mm            |
| Impedance                     | 75 Ohm            |
| Insulation material           | PE                |
| Material                      | PVC               |
| Number of products in package | 1 pcs             |
| Packaging                     | Envelope          |
| Shielding                     | Double Shielded   |
| Signal to Noise Ratio         | 90 dB             |
| SmartLife                     | No                |

### Packaging information

|                     |                    |
|---------------------|--------------------|
| Brand               | Nedis              |
| Order code          | CSGP40000WT15      |
| EAN single product: | 5412810281848      |
| EAN Inner carton:   | 5412810361922      |
| EAN Outer carton:   | 5412810348169      |
| Packaging           | Envelope           |
| Package contents    | 1x Coax Cable 90dB |

| Quantity | L x    | W x    | H (mm) | Weight  |
|----------|--------|--------|--------|---------|
| 1        | 30 mm  | 230 mm | 55 mm  | 54 g    |
| 50       | 435 mm | 90 mm  | 490 mm | 3000 g  |
| 200      | 455 mm | 390 mm | 510 mm | 13240 g |

