

## Datasheet | SMA Cable

## SMA Male | SMA Female | Gold Plated | 50 Ohm | Single Shielded | 5.00 m | Round | PVC | Black | Envelope

Brand: Nedis | Article number: CSGP02010BK50 | Product EAN number: 5412810282500

| Product specifications        |                 |
|-------------------------------|-----------------|
| Cable design                  | Round           |
| Cable length                  | 5.00 m          |
| Cable mantle material         | PVC             |
| Cable mantle size             | 2.8 mm          |
| Cable type                    | SMA             |
| Colour                        | Black           |
| Conductor diameter            | 7 x 0.16 mm     |
| Conductor material            | Bare Copper     |
| Connector A                   | SMA Male        |
| Connector B                   | SMA Female      |
| Connector design - side A     | Straight        |
| Connector design - side B     | Straight        |
| Connector material            | Metal           |
| Connector plating             | Gold Plated     |
| Impedance                     | 50 Ohm          |
| Number of products in package | 1 pcs           |
| Packaging                     | Envelope        |
| Shielding                     | Single Shielded |
| SmartLife                     | No              |

| Packaging information |               |  |  |
|-----------------------|---------------|--|--|
| Brand                 | Nedis         |  |  |
| Order code            | CSGP02010BK50 |  |  |
| EAN single product:   | 5412810282500 |  |  |
| EAN Inner carton:     | 5412810361724 |  |  |
| EAN Outer carton:     | 5412810347964 |  |  |
| Packaging             | Envelope      |  |  |
| Package contents      | Antenna Cable |  |  |

| Lx     | Wx              | H (mm)                       | Weight  |
|--------|-----------------|------------------------------|---|
| 30 mm  | 230 mm          | 80 mm                        | 84 g  |
| 435 mm | 95 mm           | 485 mm                       | 4460 g  |
| 445 mm | 210 mm          | 495 mm                       | 9580 g  |
|        | 30 mm<br>435 mm | 30 mm 230 mm<br>435 mm 95 mm | Lx W x H (mm)   30 mm 230 mm 80 mm   435 mm 95 mm 485 mm   445 mm 210 mm 495 mm |





