

LED Batten Light | 600 mm | 1050 lm | 4000 K | 11 W | IP65



Product specifications BTTN11W60:

Adjustment possibilities	Not adjustable
Beam angle	125 °
Body material	Polycarbonate
Colour	White
Colour consistency (SDCM)	≤ 6
Colour rendering index (Ra)	≥ 80
Colour temperature	4000 K
Dimmable	No
Energy class	A+
Energy consumption per 1000 hours	11 kWh
Especially for bathroom	No
Indoor / Outdoor	Indoor
Input voltage	220 - 240 V AC 50/60 Hz
Interconnectable	Yes, per type
IP rating	IP65
Lamp finish	Clear

Lamp included	Integrated
Length	600 mm
Light colour	Cool White
Lighting control	Wall Switch
Lumen maintenance factor	70.0 %
Material	Polycarbonate
Maximum power consumption	11 W
Motion sensor	No
Number of products in package	1 pcs
Number of switching cycles	≥ 20000 Switching Cycles
Operating temperature range	-20 - 50 °C
Place of lighting	Ceiling
	Wall
Power factor	≥ 0.9
Power source type	Mains Powered
Rated life time of lamp	25000 h

Rated luminous flux	1050 lm
Rated Peak Intensity in Candela	N/A
SmartLife	No
Starting time	0.5s
Technology	LED
Warm-up time to 60% light	Instant Full Light (1 s)
Wattage	11 W
Wattage equivalent	75 W

Packaging information:

Brand	Nedis
Order code	BTTN11W60
EAN single Product	5412810284610
EAN Inner Carton	
EAN Outer Carton	5412810377145
Package contents	Batten fixture Mounting materials

Read more online

Quantity	L x	W x	H (mm)	Weight
1	70 mm	65 mm	650 mm	562 g
6	220 mm	160 mm	665 mm	3800 g

