

LED Batten Light | 1200 mm | 4400 lm | 4000 K | 43 W | IP65



Product specifications BTTN43W120:

Adjustment possibilities	Not adjustable	Lamp included	Integrated	Rated luminous flux	4400 lm
Beam angle	125 °	Length	1200 mm	Rated Peak Intensity in Candela	N/A
Body material	Polycarbonate	Light colour	Cool White	SmartLife	No
Colour	White	Lighting control	Wall Switch	Starting time	0.5s
Colour consistency (SDCM)	≤ 6	Lumen maintenance factor	70.0 %	Technology	LED
Colour rendering index (Ra)	≥ 80	Material	Polycarbonate	Warm-up time to 60% light	Instant Full Light (1 s)
Colour temperature	4000 K	Maximum power consumption	43 W	Wattage	43 W
Dimmable	No	Motion sensor	No	Wattage equivalent	247 W
Energy class	A+	Number of products in package	1 pcs		
Energy consumption per 1000 hours	43 kWh	Number of switching cycles	≥ 20000 Switching Cycles		
Especially for bathroom	No	Operating temperature range	-20 - 50 °C		
Indoor / Outdoor	Indoor	Place of lighting	Ceiling		
Input voltage	220 - 240 V AC 50/60 Hz		Wall		
Interconnectable	Yes, per type	Power factor	≥ 0.9		
IP rating	IP65	Power source type	Mains Powered		
Lamp finish	Clear	Rated life time of lamp	25000 h		

Packaging information:

Brand	Nedis
Order code	BTTN43W120
EAN single Product	5412810287697
EAN Inner Carton	
EAN Outer Carton	5412810377176
Packaging	Wrap
Package contents	Batten fixture Mounting materials

Read more online

Quantity	L x	W x	H (mm)	Weight
1	90 mm	70 mm	1245 mm	1100 g
6	285 mm	160 mm	1255 mm	7420 g

