

# Datasheet | LED Batten Light

**1200 mm | 4400 lm | 4000 K | 43 W | IP65**

Brand: Nedis | Article number: BTTN43W120 | Product EAN number: 5412810287697

## Product specifications

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Adjustment possibilities          | <b>Not adjustable</b>           |
| Beam angle                        | <b>125 °</b>                    |
| Body material                     | <b>Polycarbonate</b>            |
| Colour                            | <b>White</b>                    |
| Colour consistency (SDCM)         | <b>≤ 6</b>                      |
| Colour rendering index (Ra)       | <b>≥ 80</b>                     |
| Colour temperature                | <b>4000 K</b>                   |
| Dimmable                          | <b>No</b>                       |
| Energy class                      | <b>A+</b>                       |
| Energy consumption per 1000 hours | <b>43 kWh</b>                   |
| EPREL ID                          | <b>889717</b>                   |
| Especially for bathroom           | <b>No</b>                       |
| Indoor / Outdoor                  | <b>Indoor</b>                   |
| Input voltage                     | <b>220 - 240 V AC 50/60 Hz</b>  |
| Interconnectable                  | <b>Yes, per type</b>            |
| IP rating                         | <b>IP65</b>                     |
| Lamp finish                       | <b>Clear</b>                    |
| Lamp included                     | <b>Integrated</b>               |
| Length                            | <b>1200 mm</b>                  |
| Light colour                      | <b>Cool White</b>               |
| Lighting control                  | <b>Wall Switch</b>              |
| Lumen maintenance factor          | <b>70.0 %</b>                   |
| Material                          | <b>Polycarbonate</b>            |
| Maximum power consumption         | <b>43 W</b>                     |
| Motion sensor                     | <b>No</b>                       |
| Number of products in package     | <b>1 pcs</b>                    |
| Number of switching cycles        | <b>≥ 20000 Switching Cycles</b> |
| Operating temperature range       | <b>-20 - 50 °C</b>              |
| Place of lighting                 | <b>Ceiling</b>                  |
|                                   | <b>Wall</b>                     |
| Power factor                      | <b>≥ 0.9</b>                    |
| Power source type                 | <b>Mains Powered</b>            |
| Rated life time of lamp           | <b>25000 h</b>                  |
| Rated luminous flux               | <b>4400 lm</b>                  |

Rated peak intensity in candela

**N/A**

SmartLife

**No**

Starting time

**0.5s**

Technology

**LED**

Warm-up time to 60% light

**Instant Full Light (1 s)**

Wattage

**43 W**

## Packaging information

|                     |                           |
|---------------------|---------------------------|
| Brand               | <b>Nedis</b>              |
| Order code          | <b>BTTN43W120</b>         |
| EAN single product: | <b>5412810287697</b>      |
| EAN Inner carton:   |                           |
| EAN Outer carton:   | <b>5412810377176</b>      |
| Packaging           | <b>Wrap</b>               |
| Package contents    | <b>Batten fixture</b>     |
|                     | <b>Mounting materials</b> |

| Quantity | L x    | W x    | H (mm)  | Weight |
|----------|--------|--------|---------|--------|
| 1        | 90 mm  | 70 mm  | 1245 mm | 1100 g |
| 6        | 285 mm | 160 mm | 1255 mm | 7420 g |

