



# Datasheet | IEC (Coax) CAT6 Combi

**RG58 | 75 Ohm | Double Shielded | ECA | 100.0 m | Round | White | Reel**

Brand: Nedis | Article number: CSGR4500WT1000 | Product EAN number: 5412810320370

## Product specifications

|                               |                 |
|-------------------------------|-----------------|
| Cable design                  | Round           |
| Cable length                  | 100.0 m         |
| Cable mantle material         | PVC             |
| Cable mantle size             | 10.4 mm         |
| Cable type                    | Coax / Cat6     |
| Coax type                     | RG58            |
| Colour                        | White           |
| Conductor diameter            | 0.58 mm         |
| Conductor material            | OFC             |
| CPR class                     | ECA             |
| Dielectric diameter           | 2.6 mm          |
| Frequency                     | 250 MHz         |
| Impedance external speaker    | 75 Ohm          |
| Insulation material           | PE              |
| Material                      | PVC             |
| Maximum bandwidth             | 1 Gbps          |
| Number of products in package | 1 pcs           |
| Packaging                     | Reel            |
| Shielding                     | Double Shielded |
| SmartLife                     | No              |

## Packaging information

|                     |                                        |
|---------------------|----------------------------------------|
| Brand               | Nedis                                  |
| Order code          | CSGR4500WT1000                         |
| EAN single product: | 5412810320370                          |
| EAN Inner carton:   |                                        |
| EAN Outer carton:   |                                        |
| Packaging           | Reel / Rol                             |
| Package contents    | 1x IEC (Coax) CAT6 Combi Cable on reel |

| Quantity | L x    | W x    | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1        | 270 mm | 250 mm | 275 mm | 7600 g |

