

LED Batten Light | 600 mm | 1320 lm | 4000 K | 12 W | IP65



Product specifications BTTNT812W60:

Adjustment possibilities	Not adjustable	Lamp included	Integrated	Rated luminous flux	1320 lm
Beam angle	125 °	Length	600 mm	Rated peak intensity in candela	N/A
Body material	Polycarbonate	Light colour	Cool White	SmartLife	No
Colour	White	Lighting control	Wall Switch	Starting time	0.5s
Colour consistency (SDCM)	≤ 6	Lumen maintenance factor	70.0 %	Technology	LED
Colour rendering index (Ra)	≥ 80	Material	Polycarbonate	Warm-up time to 60% light	Instant Full Light (1 s)
Colour temperature	4000 K	Maximum power consumption	11 W	Wattage	12 W
Dimmable	No	Motion sensor	No	Wattage equivalent	75 W
Energy class	E	Number of products in package	1 pcs		
Energy consumption per 1000 hours	11 kWh	Number of switching cycles	≥ 20000 Switching Cycles		
Especially for bathroom	No	Operating temperature range	-20 - 50 °C		
Indoor / Outdoor	Indoor	Place of lighting	Ceiling		
Input voltage	220 - 240 V AC 50/60 Hz		Wall		
Interconnectable	Yes, per type	Power factor	≥ 0.9		
IP rating	IP65	Power source type	Mains Powered		
Lamp finish	Clear	Rated life time of lamp	25000 h		

Packaging information:

Brand	Nedis
Order code	BTTNT8-12W60
EAN single Product	5412810336999
EAN Inner Carton	
EAN Outer Carton	
Packaging	Wrap
Package contents	Batten fixture Mounting materials

Read more online

Quantity	L x	W x	H (mm)	Weight
1	70 mm	70 mm	655 mm	475 g
6	225 mm	160 mm	665 mm	3300 g

