



Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 3.00 m | Round | PVC | White | Label



Product specifications CSGL40020WT30:

Cable design	Round	Insulation material	PE
Cable length	3.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	6.0 mm	Packaging	Label
Cable type	Coax	Shielding	Quad Shielded
Colour	White	Signal to Noise Ratio	120 dB
Conductor diameter	0.50 mm	SmartLife	No
Conductor material	OFC		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Straight		
Connector design - side B	Straight		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	3.1 mm		
Impedance external speaker	75 Ohm		

Packaging information:

Brand	Nedis
Order code	CSGL40020WT30
EAN single Product	5412810425846
EAN Inner Carton	5412810440719
EAN Outer Carton	5412810440726
Packaging	Label
Package contents	1x Coax Cable 120dB

Quantity	L x	W x	H (mm)	Weight
1	165 mm	220 mm	25 mm	145 g
50	330 mm	240 mm	470 mm	7895 g
100	340 mm	510 mm	485 mm	16900 g

