

Coax Cable | IEC (Coax) Male | IEC (Coax) Female | Nickel Plated | 120 dB | 75 Ohm | Quad Shielded | 3.00 m | Round | PVC | White | Box



Product specifications CSGB40120WT30:

Cable design	Round	Insulation material	PE
Cable length	3.00 m	Material	PVC
Cable mantle material	PVC	Number of products in package	1 pcs
Cable mantle size	6.0 mm	Packaging	Box
Cable type	Coax	Shielding	Quad Shielded
Colour	White	Signal to Noise Ratio	120 dB
Conductor diameter	0.50 mm	SmartLife	No
Conductor material	OFC		
Connector A	IEC (Coax) Male		
Connector B	IEC (Coax) Female		
Connector design - side A	Angled 90°		
Connector design - side B	Angled 90°		
Connector material	PVC		
Connector plating	Nickel Plated		
Dielectric diameter	3.1 mm		
Impedance external speaker	75 Ohm		

Packaging information:

Brand	Nedis
Order code	CSGB40120WT30
EAN single Product	5412810425938
EAN Inner Carton	5412810444403
EAN Outer Carton	5412810444410
Packaging	Box
Package contents	1x Coax Cable 120dB

Quantity	L x	W x	H (mm)	Weight
1	35 mm	230 mm	85 mm	168 g
10	225 mm	110 mm	335 mm	1900 g
60	350 mm	360 mm	520 mm	12500 g

