



# Datasheet | Satellite & Antenna

## F Male | F Male | Nickel Plated | 75 Ohm | Double Shielded | 1.00 m | Round | PVC | White | Label

Brand: Nedis | Article number: CSG41000WT10 | Product EAN number: 5412810426133

### Product specifications

|                               |                 |
|-------------------------------|-----------------|
| Cable design                  | Round           |
| Cable length                  | 1.00 m          |
| Cable mantle material         | PVC             |
| Cable mantle size             | 5.0 mm          |
| Cable type                    | F               |
| Colour                        | White           |
| Conductor diameter            | 0.50 mm         |
| Conductor material            | CCS             |
| Connector A                   | F Male          |
| Connector B                   | F Male          |
| Connector design - side A     | Straight        |
| Connector design - side B     | Straight        |
| Connector material            | Zinc            |
| Connector plating             | Nickel Plated   |
| Dielectric diameter           | 2.7 mm          |
| Impedance external speaker    | 75 Ohm          |
| Insulation material           | PE              |
| Material                      | PVC             |
| Number of products in package | 1 pcs           |
| Packaging                     | Label           |
| Shielding                     | Double Shielded |
| SmartLife                     | No              |

### Packaging information

|                     |               |
|---------------------|---------------|
| Brand               | Nedis         |
| Order code          | CSGL41000WT10 |
| EAN single product: | 5412810426133 |
| EAN Inner carton:   | 5412810431816 |
| EAN Outer carton:   | 5412810437276 |
| Packaging           | Label         |
| Package contents    | 1x Coax Cable |

| Quantity | L x    | W x    | H (mm) | Weight |
|----------|--------|--------|--------|--------|
| 1        | 15 mm  | 185 mm | 120 mm | 37 g   |
| 50       | 225 mm | 210 mm | 255 mm | 2040 g |
| 200      | 280 mm | 425 mm | 470 mm | 9480 g |

